



US010499622B2

(12) **United States Patent**  
**Braun et al.**

(10) **Patent No.:** **US 10,499,622 B2**  
(45) **Date of Patent:** **Dec. 10, 2019**

(54) **BOW FISHING REEL WITH REDUCED FRICTION PAYOUT**

(71) Applicant: **AMS, LLC**, Stratford, WI (US)

(72) Inventors: **Jeff Braun**, Stratford, WI (US); **Tim Morines**, Abbotsford, WI (US)

(73) Assignee: **AMS, LLC**, Stratford, WI (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 184 days.

(21) Appl. No.: **15/689,105**

(22) Filed: **Aug. 29, 2017**

(65) **Prior Publication Data**

US 2019/0059344 A1 Feb. 28, 2019

(51) **Int. Cl.**

**A01K 89/01** (2006.01)  
**A01K 81/00** (2006.01)  
**F41B 5/14** (2006.01)  
**A01K 89/08** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A01K 81/00** (2013.01); **A01K 89/0102** (2013.01); **A01K 89/0108** (2013.01); **A01K 89/081** (2015.05); **F41B 5/1488** (2013.01)

(58) **Field of Classification Search**

CPC ..... A01K 81/00; A01K 89/01025; A01K 89/0108; A01K 89/08; F41B 5/1488  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,773,655 A \* 12/1956 Mandolf ..... A01K 89/03 242/232  
3,000,586 A \* 9/1961 Mandolf ..... A01K 89/0102 242/238

3,074,665 A \* 1/1963 Morrow ..... A01K 89/0102 242/240  
3,823,502 A \* 7/1974 Countryman ..... A01K 89/08 43/20  
3,858,822 A \* 1/1975 Wood ..... A01K 89/0102 242/239  
4,309,974 A \* 1/1982 Carter ..... F41B 5/1488 124/23.1  
4,383,516 A 5/1983 LaSee  
6,375,107 B1 4/2002 Wong  
6,433,703 B1 \* 8/2002 Tucker ..... A01K 89/0102 340/815.5  
6,634,350 B2 10/2003 LaSee  
6,796,522 B2 9/2004 Braun  
8,579,222 B1 \* 11/2013 Alvarez ..... A01K 89/017 242/224  
9,383,160 B1 \* 7/2016 White ..... A01K 89/006  
9,560,840 B2 2/2017 Braun et al.  
D790,657 S 6/2017 Noble et al.  
10,264,771 B2 \* 4/2019 Braun ..... A01K 89/0108  
2003/0140912 A1 \* 7/2003 LaSee ..... F41B 5/1488 124/86

(Continued)


Primary Examiner — Emmanuel M Marcelo

(74) Attorney, Agent, or Firm — Boyle Fredrickson S.C.

(57) **ABSTRACT**

A reel suitable for bow fishing and the like provides a cowling covering a reel with a wide opening to reduce frictional restraint on high-speed paying out of the line with the flight of the arrow. An optional guide arm may be used to minimize line diversion and hence friction during line payout while absorbing forces when the line is retracted permitting use of a lighter cowling design without loss of strength. A high torque bevel gear transmission and safety lighting is further provided.

**16 Claims, 8 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2011/0278860 A1\* 11/2011 Lupinacci ..... A01K 87/007  
290/1 R  
2012/0285430 A1 11/2012 Dunlop et al.  
2014/0090287 A1\* 4/2014 Olson ..... A01K 97/01  
43/17  
2014/0332615 A1\* 11/2014 Braun ..... A01K 89/0108  
242/236  
2015/0354915 A1\* 12/2015 Woods, Jr. .... F41B 5/1488  
124/86  
2017/0027145 A1 2/2017 Braun et al.  
2017/0295768 A1\* 10/2017 Noble ..... A01K 89/006  
2017/0367310 A1\* 12/2017 Braun ..... A01K 89/006

\* cited by examiner






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B






FIG. 7








FIG. 10




FIG. 11

## BOW FISHING REEL WITH REDUCED FRICTION PAYOUT

### BACKGROUND OF THE INVENTION

The present invention relates to a reel for winding and storing fishing line or the like and more particularly to a reel that provides rapid payout of the fishing line, for example, as required when the reel is used for bow fishing.

In bow fishing, an arrow is fitted with a lightweight but sturdy line which may pay out behind the arrow when the arrow is shot from a bow. The line allows the arrow, and/or arrow and fish, to be retrieved after the shot.

It is important that the line be stored without tangling before release of the arrow and yet be able to pay out rapidly with little resistance when the arrow is released. Conventional reels which rotate to wind or unwind line present substantial rotational inertia that can interfere with free flight of the arrow.

These problems of line storage and release are addressed in a novel bow fishing reel described in U.S. Pat. No. 4,383,516, assigned to the assignee of the present invention, in which the line is loosely coiled in a bottle. After the line is pulled from the bottle by the arrow, opposed rubber rollers at the mouth of the bottle clamp together about the line and push it into the bottle under the urging of a geared crank handle. The line is stored without winding in a loose mass within the bottle that nevertheless resists tangling.

An alternative to the above design can be found in conventional spin casting reels, which are sometimes used for bow fishing, for example, the type described in U.S. Pat. No. 6,375,107, in which the axis of the spool about which the line is wound is parallel to the direction that the line pays out after arrow release. As the line pays out, the line slips over the edge of the reel unwinding without rotation of the reel or the need to overcome a corresponding rotational inertia of the reel. A cowling fits over the reel and provides a central aperture for corralling the line along a center line of the reel when it is wound back on the reel.

### SUMMARY OF THE INVENTION

The present inventors have recognized that in bow fishing, deflection of the line, as it pays over the edge of the reel and passes through the cowling opening to follow a high-speed arrow, can substantially impede the line reducing arrow distance and velocity. To remedy this problem, the invention provides a bow fishing reel having an extremely wide aperture cowling substantially eliminating contact between the cowling and the line as the line pays out. In one embodiment, an additional outrigger guide arm works in tandem with the wide aperture to prevent contact between the line and aperture. The outrigger arm may extend in front of the aperture by substantial distance to limit the deflection angles of the line around the reel and outrigger arm aperture, further reducing line friction.

Specifically, then, the present invention in one embodiment provides a fishing line reel having a frame adapted for attachment to a bow and a line spool rotatable with respect to the frame about a first axis to wind fishing line on the line spool around the first axis. The line spool provides a front rim extending radially about the first axis and the fishing line passes over the front rim during payout of the fishing line. A winder having a crank arm rotatable by a user may rotate the line spool around the first axis, and a cowling may be supported by the frame to surround the line spool, the cowling having an opening at a first end to allow payout of

the fishing line along the first axis. The opening in the cowling may be substantially equal in diameter to a diameter of the front rim of the reel.

It is thus a feature of at least one embodiment of the invention to reduce deflection of the line by the cowling thereby minimizing frictional contact between the bow fishing line and the cowling during rapid payout of the bow fishing line during the flight of the arrow.

The reel may further include a guide arm supported by the frame and having a portion extending beyond the opening of the cowling along the first axis to receive the fishing line therethrough guiding the fishing line to prevent contact between the opening and the fishing line when the fishing line is in tension.

It is thus a feature of at least one embodiment of the invention to eliminate contact between the cowling and the line when the line is under tension reducing unnecessary friction on the line and allowing a lighter cowling design.

The guide arm may be positioned so that the fishing line in tension is diverted by the guide arm by a deflection angle with respect to the first axis of greater than 135 degrees and desirably greater than 150 degrees.

It is thus a feature of at least one embodiment of the invention to reduce contact normal forces and thus friction by avoiding sharp deflection angles.

The diameter of the opening in the cowling may be greater than 1.5 inches and/or the opening in the cowling may be at least 50 percent of the cowling diameter. In one embodiment, the line spool may have a front rim extending radially about the first axis, and the fishing line may pass over the front rim during payout of the fishing line, and the opening may be substantially equal in diameter to a diameter of the front rim.

It is thus a feature of at least one embodiment of the invention to provide a wide opening cowling allowing release of the fishing line over the edge of the reel for high-speed payout without the need for overcoming reel inertia.

The guide arm may attach to the frame without direct contact with the cowling.

It is thus a feature of at least one embodiment of the invention to remove forces from the cowling allowing a lighter weight cowling design.

The guide arm may receive the fishing line through an aperture in a distal end of the guide arm removed from the frame and aligned with the first axis.

It is thus a feature of at least one embodiment of the invention to center the fishing line with the rotation axis of the reel for improved line payout and winding.

The crank arm may communicate with the line spool through a mechanical path through first and second perpendicular shafts each holding mutually engaging bevel gears, and an end of the first perpendicular shaft may be supported by a circumferential groove positioned on the second perpendicular shaft against forces of separation of the bevel gears.

It is thus a feature of at least one embodiment of the invention to provide a more robust right-angle drive allowing convenient placement of the crank to the side of the reel by supporting the shaft holding one bevel gear at both ends of the shaft instead of in a cantilevered fashion normally required because the shaft axes intersect.

The first perpendicular shaft may be supported against the second perpendicular shaft via a metal ball received in a socket in the end of the first perpendicular shaft and in the groove of the second perpendicular shaft.

It is thus a feature of at least one embodiment of the invention to provide a low friction "floating support" allowing the use of the second shaft to support the first shaft in a small space where conventional journal bearings would not be practical.

The fishing line reel may include a line catch for catching the fishing line to wind the fishing line about the line spool with rotation of the crank arm when the line catch is in an engaged position and for freeing the fishing line so that the fishing line does not wind about the line spool with the rotation of the crank arm when the line guide is in an unengaged position. A handle may extend from a rear of the housing substantially along the first axis and may be operable by the user to move the line guide from the unengaged position to the engaged position when the handle moves between a released position and an actuated position, and the handle may be a T-handle providing finger grip portions extending in opposite directions perpendicular to the axis and may include a pivot allowing the finger grip portions to swing within a vertical plane to align with a force applied by a user's fingers to the finger grip portions.

It is thus a feature of at least one embodiment of the invention to provide two-fingered engagement of the handle while improving user comfort by accommodating any slight angular offset between the applied force and the first axis.

The fishing line reel may include a brake system applying a sliding frictional force to the line spool when the handle is in the actuated position, the sliding frictional force being controlled by movement of a user accessible operator. The brake system may include a toothed clutch connecting the rear rim to a brake disk when the handle moves to an actuated position, the brake disk slidably engaging a stationary pad fixed with respect to the frame and pressing against the brake disk according to movement of the operator.

It is thus a feature of at least one embodiment of the invention to provide control of the reel friction independent of engagement of the clutch so that the reel may be quickly actuated by the T-handle to a predetermined level of frictional slippage.

The crank arm may include a rotatable crank knob for grasping by a user and may further include a battery-powered lamp within at least one of the cowling and the rotatable crank knob.

It is thus a feature of at least one embodiment of the invention to provide improved visibility of the components of the reel, for example, during twilight or nighttime fishing or both.

These particular objects and advantages may apply to only some embodiments falling within the claims and thus do not define the scope of the invention.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a fragmentary perspective view of a bow riser portion of a bow having the reel of the present invention attached thereto by means of an adjustable mounting system;

FIG. 2 is a side elevational cross-section of the reel of FIG. 1 showing positioning of the control handle forward in the released position so that the line guide used for winding line around the line spool is retracted and the line spool is free to rotate;

FIG. 3 is a figure similar to that of FIG. 2 showing positioning of the control handle rearward in the actuated position so that the line guide used for winding line around the line spool is extended for engaging the fishing line and the line spool is locked against rotation;

FIG. 4 is a fragmentary exploded view of the mechanism of the reel of FIG. 1 showing operation of the control handle to extend or retract the line guide within a fishing line deflector and showing positioning of a wave washer used to provide a controlled friction clutch and engagement tabs providing a dog clutch between the housing and the line spool;

FIG. 5 is a partial elevational cutaway of the reel of FIG. 1 showing dimensions of the wide cowling aperture and a front-extending outrigger arm for improved payout and reduced friction and cross axial forces on the cowling;

FIGS. 6a and 6b are vector force diagrams showing the reduced cross axial and hence frictional forces provided by the arrangement of FIG. 5;

FIG. 7 is a rear perspective view of the reel of FIG. 1 with the housing removed to show the inner gear train;

FIG. 8 is a fragmentary perspective view of the reel, tooth plate and friction pad used to provide simple control of tension on the line;

FIG. 9 is an exploded perspective view of the bevel gears interconnecting the crank of the reel to the reel driveshaft by a floating ball and track joint;

FIG. 10 is an end view of the reel showing slots for engagement of LED light sticks for illuminating the reel; and

FIG. 11 is a cross-sectional view of the crank handle also receiving a light stick for illumination thereof.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to FIG. 1, a bow fishing how 10 may include a bow frame 12 presenting a bow riser 14 providing a grip 16 for gripping by the bow hand of the user 33. The bow riser 14 may provide an arrow shelf 17 above the grip 16 for supporting the arrow shaft (not shown) before release of the arrow for travel generally along axis 19'.

A fishing line reel 20 for storing and paying out fishing line 22 may be attached to the bow riser 14 near the grip 16 by means of a mounting fixture 21 to be positioned generally proximate to and in front of the bow riser 14 to provide a payout axis 19' generally parallel to axis 19. The fishing line 22 used in this capacity may be, for example, a braided rather than monofilament line, for example, a braided Dacron roughly 1/32 inches in diameter or smaller ranging from 50-pound test to 150-pound test, that may be readily distinguished from, for example, a fly casting line by its greater strength and substantially greater outer diameter.

The fishing line reel 20 may have a reel housing 23 providing a frame attached to a vertically descending mount 24 attached to lower clamp jaws 26. The clamp jaws 26 connect with a picatinny rail 31a of the mounting fixture 21 being one of three picatinny rails 31a-c available on the mounting fixture 31 as will be discussed below. The mounting fixture 21 may be attached to a mounting bushing 39 extending forward from the riser 14 below the grip 16 and attached to the riser 14 by means of a threaded bore 27 extending therethrough generally parallel to axis 19'. The mounting fixture 21 will be discussed in greater detail below.

The reel housing 23 is positioned to allow the fishing line 22 extending along an axis 19 parallel to axis 19' to be proximately below but vertically aligned with axis 19'. Ideally the axis 19' of the fishing line 22 is roughly centered on the grip 16 significantly limiting torque on the grip 16 when tension is applied to the fishing line 22.

A spool control T-handle 35 extends rearwardly from the reel housing 23 generally aligned with axis 19 and posi-

tioned close to the grip 16 so that the spool control T-handle 35 may be easily operated by fingers of a hand of the user 33 holding the grip 16. When not operated by the user, the control T-handle 35 will be in a forward released position as shown.

A single-handled crank arm 30 may extend from a side of the housing 23 to be operated by the user to rotate a crankshaft (not shown in FIG. 1) about axis 32 perpendicular to axis 19. The crank arm 30 may include rotating grips 34 on its end as is generally understood in the art.

In normal use, a reel cowling 36 may attach to the housing 23 to protect and cover an internal winding mechanism (to be discussed below) and to provide a forward opening 38 through which the fishing line 22 exits generally along the axis 19.

Referring now to FIGS. 2 and 4, as noted above, the crank arm 30 may attach to a crankshaft 40 extending along axis 32 through a support bearing 42 held in a right side portion of the housing 23. After passing through a ratchet mechanism 45 or similar one-way clutch allowing only clockwise force to be applied to the crankshaft 40 by the crank arm 30, the crankshaft 40 may attach to bevel gear 44. The bevel gear 44 may engage with and drive a smaller pinion gear 46 attached to a shaft 48 formed by inter-engaging gears, the latter turning a shaft 48 extending generally parallel to axis 19 to rotate the shaft 48 with rotation of the crank arm 30 with a step up in rotational rate caused by the gear ratio between bevel gear 44 and smaller pinion gear 46 and the shaft 48. A second ratchet 47 and pawl 49 may be attached to the shaft 48 to augment ratchet 45.

The shaft 48 extends forward from and out of the housing 23 to pass progressively through a tooth plate 51 having teeth 77, a wave washer spring 50, a fishing line spool 52, a bearing 54, a rear fishing line deflector 56, and a front fishing line deflector 60. In this embodiment, the tooth plate 51 is free to rotate as constrained by a friction pad as will be discussed below. A key surface 63 (or other spline-type sliding attachment) on the shaft 48 is received by corresponding key surfaces 64 on the rear and front fishing line deflectors 56 and 60 so that the rear and front fishing line deflectors 56 and 60 rotate with the shaft 48 but are free to slide within a limited range axially along axis 19' with respect to the shaft 48. Forward axial movement of the front fishing line deflector 60 on the shaft 48 is restrained by a stop (not shown).

Each of the front fishing line deflector 60 and rear fishing line deflector 56 provide substantially smooth circular outer peripheries providing a front rim to a spool 52 and may allow the fishing line 22 to slide around axis 19 when paying off of the fishing line spool 52 as will be described below.

The fishing line spool 52 has a generally frustoconical hub 70 tapering to a larger diameter from rear to front (toward the opening 38) and flanked by front and rear radially-extending flanges 72 and 74 which serve to retain coiled fishing line 22 on the hub 70. The flange 72 fits against the rear fishing line deflector 56 which forms a rim to the spool 52 around which the line 22 may pay out. The front edge of the hub 70 may include a hole (not shown) that allows the fishing line 22 to be tied positively to the hub 70 without slipping with rotation of the fishing line spool 52.

The rear flange 72 may include teeth 75 that may engage corresponding teeth 77 on a tooth plate 51 attached to the housing 23 when wave washer spring 50 is fully compressed, this compression allowing the flange 74 to move rearward as will be discussed into engagement with the tooth plate 51.

The T-handle 35 may attach through an opening in the rear of the housing 23 generally aligned with axis 19' and may attach to a through shaft 80 that passes forward through a hollow bore in shaft 48 extending axially through the shaft 48 along axis 19. The through shaft 80 may thus slide smoothly through the hollow bore of the shaft 48 with movement of the T-handle and without interference with rotation of the shaft 48. An end of the through shaft 80 extending through the shaft 48 may be attached to an end cap 82 which may press against the front surface of the front fishing line deflector 60 to provide compressive force along axis 19 without constraining the rotation of the front fishing line deflector 60 when the T-handle is pulled back.

Three line catch pins 84 are embedded in the front fishing line deflector 60 to extend from a rear of the periphery of the front fishing line deflector 60 generally parallel to axis 19 but displaced therefrom at equal angles. The line catch pin 84 may be received within a loose, aligned bore formed in the rear fishing line deflector 56 to slide therethrough. The front fishing line deflector 60 and the rear fishing line deflector 56 may be spring biased apart.

The action of the wave washer spring 50 and spring biasing serves to move the T-handle to the forward released position when it is not pulled back by the user as shown in FIG. 2. In this released position, springs separate the rear fishing line deflector 56 from the front fishing line deflector 60 pulling the line catch pins 84 fully within the rear fishing line deflector 56 so that they may not interfere with a sliding of the fishing line 22 around the smooth, radially symmetrical outer peripheries of the line deflectors 56 and 60 during an unspooling operation. In addition, wave washer spring 50 separates the teeth 77 of the rear flange 74 and teeth 75 of the tooth plate 51 attached to the housing 23 so that the line spool 52 may freely rotate. It will be understood therefore that paying out of the fishing line 22 is facilitated by the ability of the fishing line 22 to pass freely around the fishing line deflectors 56 and 60 in an unwrapping process. In addition, the opening of the cowling 36 is greatly expanded substantially reducing the interference between the cowling 36 and the fishing line 22, and in particular, the deflection of the line 22 caused by any incidental contact between the line 22 and the edge of the opening 38 in the cowling 36 such as produces normal, frictional forces of the type described below.

Referring now to FIGS. 3 and 4, with rearward motion of the T-handle by the user, increased force of compression on wave washer spring 50 causes the teeth 75 of the flange 74 to engage teeth 77 of the tooth plate 51 to provide a dog clutch positively locking the two together and providing controlled friction with rotation of the tooth plate 51 that will be described below.

Referring still to FIGS. 3 and 4, retraction of the T-handle rearward to the actuation position also provides an extension of the line catch pins 84 from a rear surface of the rear fishing line deflector 56 so that they may catch the fishing line 22 and, with rotation driven by the crank arm 30, wrap the fishing line 22 around the fishing line spool 52 which is now held in a locked position. Control of the tension of the fishing line 22 will be a function of frictional restraint of the line spool 52 (described below) and prevention of rotation of the rear and front fishing line deflectors 56, the latter effected through the user control of the crank arm 30.

Referring momentarily again to FIG. 1, during use, an arrow slide on an arrow (not shown but as depicted in U.S. Pat. No. 6,517,453 hereby incorporated by reference) will be attached to a free end of the fishing line 22 and engage with the bowstring, for example, held by the user's right hand

(assuming a right-handed user and bow) while the user's left hand holds the grip **16**. The user's fingers will be free of the T-handle and thus when the arrow is released the fishing line **22** will be able to pay out at rapid speed. For retrieval of the arrow and fishing line **22**, the user may simply extend the fingers of the hand of the user **33** holding the bow to engage the T-handle and pull it back to extend the pins **84**. The user's right hand will then be able to operate the crank arm **30**. By simultaneous control of the crank arm **30** and the T-handle tensioning, retraction of the fishing line may be flexibly controlled.

Referring again to FIGS. **1** and **4**, the T-handle may be a handle providing wings **81** extending in opposite directions perpendicularly to shaft **80** to each receive one or more fingers of the user **33** on either side of the shaft **80** to provide for a centered retraction force. The surface of the wings **81** toward the reel **20** may be arcuate for improved comfort and finger centering at equal distance from the shaft **80**.

Referring now to FIGS. **1**, **2**, **3** and **5**, the reel cowling **36** may provide for a front opening diameter **160** through which the line **22** may pass that is substantially equal to the outside diameter **162** of the line deflectors **56** and **60** forming a front rim of the spool **52**. The front opening diameter **160** is preferably equal to the outside diameter **162** of the line deflectors **56** and **60** (plus or minus 10 percent) and generally greater than 1.5 inches or greater than two inches and preferably equal to substantially at least 2.5 inches. The diameter **160** may be at least 50 percent of the outside diameter **163** of the cowling **36** or greater than 80 percent of this outside diameter **163** which may be substantially three inches in diameter. When the line **22** is pulled tight to extend parallel to axis **19**, it may be deflected by the cowling **36** by less than a deflection angle **81** of 20 degrees. Ideally there will be substantially no deflection of the line **22** in these situations.

An outrigger arm **164** may extend forward from the mounting fixture **21** stationary with respect to the how fishing reel **20** during use and bend upward to intersect the axis **19**. At that intersection, the outrigger arm **164** may have an opening **166** generally aligned along axis **19** with the shaft **80** of the reel **20**. The opening **166** is displaced forward from the reel **20** such that when the line **22** is pulled tight through the aperture **166** and against an outer periphery of the line deflector **60**, the line is free from contact with the cowling **36**.

When the line **22** extends from the aperture **166** forward along axis **19** and is pulled tight, it has a deflection before and after aperture **166** that subtends an angle **170** greater than 135 degrees and preferably substantially equal to 155 degrees. A corresponding angle of deflection occurs as the line **22** passes over the edge of the line deflector **60** from a line trajectory generally parallel to axis **19** to a trajectory deflected inward toward the opening **166**. The deflection angle is an angle of less than or equal to 180 degrees measured in the plane of deflection.

Referring now also to FIG. **6a**, by making these subtended angles **170** closer to 180 degrees, the normal force of the line **22** on the aperture **166** or edge of the line deflector **60** is reduced reducing friction. For given opposed tension forces **172** directed along the line **22**, a reduced cross axial normal force **174** is produced. The cross axial force **174** is relevant (generally proportional) to the frictional force of contact between the line **22** and the aperture **166** or against the line deflector **60** as illustrated by vector decomposition of these forces in this figure. The large angle **170** is promoted by increasing the distance **176** between the last point of contact between the line **22** and the line deflector **60** and a point of

contact between the line **22** and the aperture **166** when compared to the typical separation distance **178** between the last point of contact between the line **22** and the line deflector **60** and the edge of the cowling **36**. This latter distance **178** occurs in reels where the line **22** is constrained by an opening in the cowling **36**. In this latter case, much smaller subtended angles **180** are provided at the deflection points of the line **22** causing much higher cross axial forces **182** greatly increasing frictional contact between the line and its guiding members of the line deflector **60** and aperture **166**. These smaller angles **180** also place higher forces on the cowling **36** such as may deform the cowling **36** or require that it be made of heavier material undesirable to the extent that it increases the overall weight of the bow. In a similar manner, the reduced deflection of the line **22** shown in FIG. **3** provides reduced frictional normal force.

Referring again to FIG. **5**, a connection between the shaft **80** extending rearward from the housing **23** and the T-handle **35** may be a pivoting connection **190** allowing an axis of symmetry **193** of the T-handle **35** to be deflected upward or downward by approximately 20 degrees. This motion allows the T-handle **35** to equalize force between fingers of the user placed on either side of the T-handle **35** to accommodate slight changes of the height of the user's grip on the bow grip **16** shown in FIG. **1**.

Referring now to FIGS. **5** and **8**, when the spool **52** is pulled backward against the force of the wave washer **50** so that the teeth **75** of the tooth plate **51** engage corresponding recesses in the rear surface of the flange **74** of the spool **52**, the spool **52** and the tooth plate **51** will rotate together, for example, with winding of the line **22** around the hub **70**. A frictional resistance on the movement of the tooth plate **51** may be imposed by means of a friction plate **192** slidably abutting a rear face of the tooth plate **51**. As so positioned, the friction plate **192** rubs against the tooth plate **51** with a normal force controlled by a threaded shaft **194** pressing the friction plate **192** against the rear surface of the tooth plate **51**. The force imposed by the threaded shaft **194** may be adjusted by rotating the threaded shaft **194** within a threaded collar **196** fixed with respect to the housing **23**. An operator knob **198** attached to an outer end of the threaded shaft **194** may be accessible to the user to allow adjustment of this compression force and hence a frictional constraint on the rotation of the spool **52** when it is locked to the tooth plate **51**.

Referring now to FIGS. **7** and **9**, bevel gears **46** and **44** rotate along mutually perpendicular and intersecting axes **32** and **19'**, (the latter generally parallel to axis **19**). Because of the close proximity of bevel gears **46** and **44** necessary for their inter-engagement, normally one of these gears must be supported in cantilevered fashion, in this case bevel gear **44**. Additional support against deflection of bevel pinion gear **46** against disengaging forces as indicated by arrow **200** moving the bevel pinion gear **46** away from bevel gear **44** is provided by a floating support ball **202** that fits within a corresponding hemi-spherical socket **204** in a cantilevered end of bevel pinion gear **46**. This support ball **202** supports the bevel pinion gear **46** against forces along arrow **200** by also being constrained in a hemi-circular groove **205** in crankshaft **40** associated with bevel gear **44**. In this way bevel pinion gear **46** may be supported by crankshaft **40** despite relative motion of these two components.

Referring now to FIGS. **10** and **11**, improved use of the reel **20** at night may be provided by placing insertion slots **206** in the front face of line deflector **60**, for example, tangentially oriented at three locations separated by 120 degrees about axis **19**. These slots **206** may receive, for

example, by snap fit, corresponding light sticks **208** having a body incorporating a switch and battery and at one end exposing an LED lamp **210**. Light sticks **208** suitable for this purpose are commercially available from a variety of sources and are sold for use in fishing bobbers and for lighting archery nooks. Placement and viewing of the light sticks **208** is facilitated by the substantial opening size of the cowling **36** (shown in FIG. **8**).

As shown in FIG. **3**, the grip **34** may be hollow and either an opaque or transparent or translucent material and may include a socket **212** for receiving and holding a light **208** for illuminating that grip **34**.

Certain terminology is used herein for purposes of reference only, and thus is not intended to be limiting. For example, terms such as “upper”, “lower”, “above”, and “below” refer to directions in the drawings to which reference is made. Terms such as “front”, “back”, “rear”, “bottom” and “side”, describe the orientation of portions of the component within a consistent but arbitrary frame of reference which is made clear by reference to the text and the associated drawings describing the component under discussion. Such terminology may include the words specifically mentioned above, derivatives thereof, and words of similar import. Similarly, the terms “first”, “second” and other such numerical terms referring to structures do not imply a sequence or order unless clearly indicated by the context.

When introducing elements or features of the present disclosure and the exemplary embodiments, the articles “a”, “an”, “the” and “said” are intended to mean that there are one or more of such elements or features. The terms “comprising”, “including” and “having” are intended to be inclusive and mean that there may be additional elements or features other than those specifically noted. It is further to be understood that the method steps, processes, and operations described herein are not to be construed as necessarily requiring their performance in the particular order discussed or illustrated, unless specifically identified as an order of performance. It is also to be understood that additional or alternative steps may be employed.

It is specifically intended that the present invention not be limited to the embodiments and illustrations contained herein and the claims should be understood to include modified forms of those embodiments including portions of the embodiments and combinations of elements of different embodiments as come within the scope of the following claims. All of the publications described herein, including patents and non-patent publications, are hereby incorporated herein by reference in their entireties.

What we claim is:

**1.** A fishing line reel providing rapid line payout comprising:

- a frame adapted for attachment to a bow;
- a line spool rotatable with respect to the frame about a first axis to wind fishing line on the line spool around the first axis;
- a winder having a crank arm rotatable by a user to rotate the line spool around the first axis;
- a cowling supported by the frame and surrounding the line spool, the cowling having an opening at a first end to allow payout of the fishing line along the first axis; and
- a guide arm supported by the frame and having a portion extending beyond the opening of the cowling along the first axis to receive the fishing line therethrough guiding the fishing line to prevent contact between the opening and the fishing line when the fishing line is in tension applied beyond the guide arm;

wherein the line spool provides a front rim extending radially about the first axis and the fishing line passes over the front rim during payout of the fishing line and wherein the opening is substantially equal in diameter to a diameter of the front rim.

**2.** The fishing line reel of claim **1** wherein the opening has a diameter within 10 percent of the diameter of the front rim.

**3.** The fishing line reel of claim **1** wherein the opening is sized so that when the fishing line is in tension along the first axis, it is diverted by the cowling by a deflection angle with respect to the first axis of less than 20 degrees.

**4.** The fishing line reel of claim **1** wherein a diameter of the opening in the cowling is greater than 1.5 inches.

**5.** The fishing line reel of claim **1** wherein the cowling is substantially cylindrical and has a cowling diameter and wherein the diameter of the opening in the cowling is at least 80 percent of the cowling diameter.

**6.** The fishing line reel of claim **1** wherein the guide arm is positioned so that the fishing line in tension is diverted by the guide arm by a deflection angle with respect to the first axis of greater than 135 degrees.

**7.** The fishing line reel of claim **6** wherein the deflection angle is greater than 150 degrees.

**8.** The fishing line reel of claim **6** wherein the line spool provides a front rim extending radially about the first axis and the fishing line passes over the front rim during payout of the fishing line and wherein the deflection angle is an angle measured between an extent of the fishing line in tension between the front rim and the guide arm and the first axis.

**9.** The fishing line reel of claim **1** wherein the guide arm is attached to the frame without direct contact with the cowling.

**10.** The fishing line reel of claim **1** wherein the guide arm receives the fishing line through an aperture in a distal end of the guide arm removed from the frame and aligned with the first axis.

**11.** The fishing line reel of claim **1** wherein the crank arm includes a rotatable crank knob for grasping by a user and further including a battery-powered lamp within at least one of the cowling and the rotatable crank knob.

**12.** A fishing line reel providing rapid line payout comprising:

- a frame adapted for attachment to a bow;
- a line spool rotatable with respect to the frame about a first axis to wind fishing line on the line spool around the first axis;
- a winder having a crank arm rotatable by a user to rotate the line spool around the first axis; and
- a cowling supported by the frame and surrounding the line spool, the cowling having an opening at a first end to allow payout of the fishing line along the first axis; wherein the line spool provides a front rim extending radially about the first axis and the fishing line passes over the front rim during payout of the fishing line and wherein the opening is substantially equal in diameter to a diameter of the front rim;
- wherein the crank arm communicates with the line spool through a mechanical path through first and second perpendicular shafts each holding mutually engaging bevel gears and wherein an end of the first perpendicular shaft is supported by a circumferential groove positioned on the second perpendicular shaft against forces of separation of the bevel gears.

**13.** The fishing line reel of claim **12** wherein the first perpendicular shaft is supported against the second perpen-

11

dicular shaft via a metal ball received in a socket in the end of the first perpendicular shaft and in the groove of the second perpendicular shaft.

14. A fishing line reel providing rapid line payout comprising:

- a frame adapted for attachment to a bow;
- a line spool rotatable with respect to the frame about a first axis to wind fishing line on the line spool around the first axis;
- a winder having a crank arm rotatable by a user to rotate the line spool around the first axis; and
- a cowling supported by the frame and surrounding the line spool, the cowling having an opening at a first end to allow payout of the fishing line along the first axis;

wherein the line spool provides a front rim extending radially about the first axis and the fishing line passes over the front rim during payout of the fishing line and wherein the opening is substantially equal in diameter to a diameter of the front rim;

wherein the winder further includes:

- a line catch for catching the fishing line to wind the fishing line about the line spool with rotation of the crank arm when the line catch is in an engaged position and for freeing the fishing line so that the fishing line does not

12

wind about the line spool with the rotation of the crank arm when the line guide is in an unengaged position; and

- a handle extending from a rear of the frame substantially along the first axis and operable by the user to move the line guide from the unengaged position to the engaged position when the handle moves between a released position and an actuated position;
- wherein the handle is a T-handle providing finger grip portions extending in opposite directions perpendicularly to the axis, the T-handle including a pivot allowing the finger grip portions to swing within a vertical plane to align with a force applied by a user's fingers to the finger grip portions.

15. The fishing line reel of claim 14 including a brake system applying a sliding frictional force to the line spool when the handle is in the actuated position, the sliding frictional force being controlled by movement of the user-accessible operator.

16. The fishing line reel of claim 15 wherein the brake system includes a toothed clutch connecting the rear rim to a brake disk when the handle moves to an actuated position, the brake disk slidably engaging a stationary pad fixed with respect to the frame and pressing against the brake disk according to movement of the operator.

\* \* \* \* \*