



(12) **United States Patent**
Floresta et al.

(10) **Patent No.:** **US 10,608,469 B2**
(45) **Date of Patent:** **Mar. 31, 2020**

(54) **METHOD AND APPARATUS FOR POWER TRANSFER TO AN INDEPENDENT MOVING CART DURING TRAVEL ALONG A TRACK**

(56) **References Cited**

(71) Applicant: **Rockwell Automation Technologies, Inc.**, Mayfield Heights, OH (US)
(72) Inventors: **John Floresta**, Commack, NY (US); **Peter Bruder**, Smithtown, NY (US); **Xikai Sun**, Shanghai (CN); **Peter M. Smit**, Mount Sinai, NY (US); **Oliver C. Haya**, Milwaukee, WI (US); **Mark R. Cooper**, Eden Prairie, MN (US); **Nanwei Yao**, Edina, MN (US)

U.S. PATENT DOCUMENTS

4,427,910 A * 1/1984 Richter H02K 3/493
310/214
5,013,929 A * 5/1991 Dhyanchand F02N 11/04
290/31

(Continued)

FOREIGN PATENT DOCUMENTS

EP 2806547 A1 11/2014
EP 3151397 A1 4/2017

(Continued)

(73) Assignee: **Rockwell Automation Technologies, Inc.**, Mayfield Heights, OH (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 63 days.

Partial European Search Report dated Jan. 7, 2019—(13) pages.

(Continued)

Primary Examiner — Rina I Duda

(21) Appl. No.: **15/719,021**

(74) *Attorney, Agent, or Firm* — Boyle Fredrickson, SC

(22) Filed: **Sep. 28, 2017**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2019/0097466 A1 Mar. 28, 2019

A system and method for providing power to independent movers traveling along a track in a motion control system without requiring a fixed connection between the mover and a power source external to the mover. In one embodiment, a sliding transformer transfers power between the track and each mover. In another embodiment, an optical transmitter transfers power between the track and an optical receiver mounted on each mover. In yet another embodiment, a generator includes a drive wheel engaging the track as each mover travels along the track. A power converter on the mover receives the power generated on and/or transmitted to the mover to control an actuator or a sensor mounted on the mover or to activate drive coils mounted on the mover to interact with magnets mounted along the track and, thereby, control motion of each mover.

(51) **Int. Cl.**
H02J 50/10 (2016.01)
B60L 15/00 (2006.01)


(Continued)

(52) **U.S. Cl.**
CPC **H02J 50/10** (2016.02); **B60L 5/005** (2013.01); **B60L 15/007** (2013.01); **H01F 38/14** (2013.01); **H02J 50/30** (2016.02); **B65G 54/02** (2013.01)

(58) **Field of Classification Search**
CPC ... B61B 3/00; B61J 1/12; B65G 47/96; B65G 17/345

See application file for complete search history.

19 Claims, 18 Drawing Sheets



(51)	<p>Int. Cl. H01F 38/14 (2006.01) H02J 50/30 (2016.01) B60L 5/00 (2006.01) B65G 54/02 (2006.01)</p>	<p>2010/0130096 A1 5/2010 Baarman et al. 2011/0043053 A1 2/2011 Shikayama et al. 2012/0145500 A1 6/2012 Staunton et al. 2012/0247925 A1 10/2012 Cooke 2014/0265645 A1* 9/2014 Jacobs H02K 41/031 310/12.15 2014/0285034 A1 9/2014 Krop et al. 2015/0048693 A1 2/2015 Prussmeier 2016/0090275 A1 3/2016 Piech et al. 2017/0183170 A1 6/2017 Wernersbach et al.</p>
(56)	<p style="text-align: center;">References Cited</p> <p style="text-align: center;">U.S. PATENT DOCUMENTS</p> <p>5,690,209 A * 11/1997 Kofoed B65G 17/345 198/370.03 5,737,211 A 4/1998 Hirai et al. 5,927,657 A * 7/1999 Takasan B61L 3/225 104/297 6,191,507 B1 2/2001 Peltier et al. 6,522,035 B1 2/2003 Smit 6,844,651 B1* 1/2005 Swift H02K 3/48 310/214 6,876,107 B2* 4/2005 Jacobs B60L 15/38 310/12.19 7,109,610 B2 9/2006 Tamai 7,559,282 B2* 7/2009 Austin B65G 17/345 104/48 7,696,651 B2 4/2010 Miyamoto 8,384,251 B2 2/2013 Shikayama et al. 8,776,694 B2* 7/2014 Rosenwinkel B65G 47/96 104/88.02 8,844,250 B2 9/2014 Nemkov et al. 9,102,336 B2* 8/2015 Rosenwinkel B61B 13/04 9,333,875 B2 5/2016 Staunton et al. 9,422,121 B2 8/2016 Staunton et al. 2003/0201862 A1 10/2003 Arntz et al. 2003/0230941 A1 12/2003 Jacobs 2009/0045773 A1 2/2009 Pandya et al.</p>	<p style="text-align: center;">FOREIGN PATENT DOCUMENTS</p> <p>GB 2463692 A 3/2010 WO 99/08359 A1 2/1999 WO 2010/129369 A2 11/2010 WO 2012/138949 A2 11/2012</p> <p style="text-align: center;">OTHER PUBLICATIONS</p> <p>Barnard et al.; Sliding Transformers for Linear Contactless Power Delivery; IEEE Transactions on Industrial Electronics, vol. 44, No. 6, Dec. 1997—(6) pages. Klontz et al.; Contactless Power Delivery System for Mining Applications; IEEE Transactions on Industry Applications, vol. 31, No. 1 Jan./Feb. 1995—(9) pages. Rockwell Automation: “Introducing iTRAK: The Intelligent Track System”; YouTube.com—(1) page, Published May 20, 2015. Rockwell Automation: “User Manual—iTRAK System”; Bulletin 2198T: Jun. 30, 2017, XP055511206, Retrieved from the Internet: URL:https://literature.rockwellautomation.com/idc/groups/literature/documents/um/2198t-um001_-en-p.pdf—(138) pages.</p> <p>* cited by examiner</p>




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22

METHOD AND APPARATUS FOR POWER TRANSFER TO AN INDEPENDENT MOVING CART DURING TRAVEL ALONG A TRACK

BACKGROUND INFORMATION

The present invention relates to motion control systems and, more specifically, to power transfer to an independent mover as it travels along a track in a motion control system incorporating multiple movers propelled along the track using a linear drive system.

Motion control systems utilizing movers and linear motors can be used in a wide variety of processes (e.g. packaging, manufacturing, and machining) and can provide an advantage over conventional conveyor belt systems with enhanced flexibility, extremely high speed movement, and mechanical simplicity. The motion control system includes a set of independently controlled "movers" each supported on a track for motion along the track. The track is made up of a number of track segments, and a linear drive system controls operation of the movers, causing the movers to travel along the track. Sensors may be spaced at fixed positions along the track and/or on the movers to provide information about the position and speed of the movers.

Each of the movers may be independently moved and positioned along the track in response to an electromagnetic field generated by the linear drive system. In a typical system, the track forms a closed path over which each mover repeatedly travels. At certain positions along the track other actuators may interact with each mover. For example, the mover may be stopped at a loading station at which a first actuator places a product on the mover. The mover may then be moved along a process segment of the track where various other actuators may fill, machine, position, or otherwise interact with the product on the mover. The mover may be programmed to stop at various locations or to move at a controlled speed past each of the other actuators. After the various processes are performed, the mover may pass or stop at an unloading station at which the product is removed from the mover. The mover then completes a cycle along the closed path by returning to the loading station to receive another unit of the product.

In certain applications, it may be desirable to provide an actuator or a sensor on the mover to interact with the product on the mover. For example, a clamp may actuate to secure the product to the mover or a sensor may detect the presence of the product on the mover. However, the actuator or sensor requires an energy source to operate. For electric actuators or sensors, the energy source may be a battery. For a hydraulic or pneumatic actuator, the energy source may be a pressurized tank. The energy source adds weight and takes up space on the mover. Further, the energy source needs to be periodically recharged.

One solution for providing energy to a mover is to provide a dedicated location along the track at which the energy is supplied. The mover stops at the dedicated location where a temporary connection to an energy source may be established. A first actuator external to the mover may engage the mover and establish an electrical, pneumatic, or hydraulic connection to the mover. A second actuator on the mover may perform the desired task, and the first actuator supplying power may subsequently disengage from the mover. This process, however, requires the mover to come to a stop at the dedicated location, wait for power to be connected, perform the desired action, and wait for the power to be disconnected before resuming motion. The additional steps required to supply power reduce the throughput of the system and the

dedicated locations limit the ability of actuators or sensors present on a mover to operate.

Thus, it would be desirable to provide an improved system for supplying power to independent movers on a track in a motion control system.

Another solution for providing energy to a mover is to provide a fixed connection to the mover. The fixed connection may be, for example, an electrical conductor or a hydraulic or pneumatic hose. A fixed connection, however, is not without certain drawbacks. The motion of the mover is typically restricted to limit the required length of the electrical conductor or hose. The number of movers must be limited and/or the motion of the mover is limited to a reciprocal motion to avoid tangling the conductors or hoses between movers.

Thus, it would be desirable to provide a method and apparatus for transmitting power to an independent mover as it travels along a track in a motion control system which eliminates a fixed connection between the mover and a power source.

Historically, the linear drive system has included multiple coils spaced along the track and magnets mounted to each of the movers. The magnets on the movers may include multiple magnet segments with alternating north and south poles oriented to face the track. Each pair of north and south poles corresponds to a pole pair in the linear drive system. The coils along the track are sequentially energized with an alternating current which establishes an electromagnetic field around the coil. The electromagnetic field interacts with the magnetic field generated by the pole pairs on the movers and is controlled to drive the movers along the track. This arrangement, however, requires power converters corresponding to the coils spaced along the track to control the current through each coil. The linear drive system may require twice as many power converters as movers present on the track and include a significant portion of idle time while no mover is present over a coil controlled by the power converter.

Thus, it would be desirable to provide a system for transmitting sufficient power to each mover to supply power to coils on the mover which, in turn, interact with magnets mounted along the track to control operation of each mover.

BRIEF DESCRIPTION

The subject matter disclosed herein describes a system and method for providing power to independent movers traveling along a track without requiring a fixed or removable connection to each mover. A power converter on the mover may regulate the power supplied to the mover to control an electrical device, such as an actuator or a sensor mounted on the mover. The power converter on the mover may also be configured to activate drive coils mounted on the mover to interact with magnets mounted along the track and, thereby, control motion of each mover. In one embodiment, a sliding transformer transfers power between the track and each mover. In another embodiment, an optical transmitter transfers power between the track and an optical receiver mounted on each mover. In yet another embodiment, a generator includes a drive wheel engaging the track as each mover travels along the track. A power converter on the mover receives the power generated on and/or transmitted to the mover to control an actuator or a sensor mounted on the mover or to activate drive coils mounted on the mover to interact with magnets mounted along the track and, thereby, control motion of each mover.

In one embodiment of the invention an apparatus for providing power to a mover in a motion control system includes multiple movers, multiple electrical devices, and a closed track. Each electrical device is mounted to one of the movers, and the closed track defining a continuous path along which each of the movers travels. Each of the movers includes a drive wheel configured to engage the closed track and to rotate as the mover travels along the closed track, a drive shaft operatively coupled to the drive wheel wherein rotation of the drive wheel causes rotation of the drive shaft, and a generator operatively coupled to the drive shaft to generate electrical power when the drive shaft rotates. The apparatus also includes a power converter having an input and an output, where the input of the power converter receives the electrical power from the generator and the output supplies power to the at least one electrical device mounted on the mover.

According to another embodiment of the invention, an apparatus for providing power to a mover in a motion control system includes a plurality of movers a plurality of electrical devices, and a closed track. At least one of the electrical devices is mounted to each of the movers, and the closed track defining a continuous path along which each of the movers travels. The apparatus also includes an optical transmitter mounted on the closed track and operative to emit light at a predefined frequency, and a plurality of optical receivers. Each optical receiver is mounted to one of the movers and is oriented to receive the light emitted by the optical transmitter as the mover travels along the closed track. A plurality of power converters are included, where each of the plurality of power converters is mounted to one of the movers and is operative to receive power from the optical receiver and to supply power to the at least one electrical device mounted on the mover.

According to yet another embodiment of the invention, an apparatus for providing power to a mover in a motion control system includes a plurality of movers, a plurality of electrical devices, and a closed track. At least one of the electrical devices is mounted to each of the plurality of movers and the closed track defines a continuous path along which each of the plurality of movers travels. A primary winding is mounted along the closed track, where the primary winding is configured to receive power from a power supply. The apparatus further includes a plurality of secondary windings and a plurality of power converters. Each secondary winding is mounted to one of the plurality of movers and is generally aligned with the primary winding as the mover travels along the closed track. An air gap separates each secondary winding from the primary winding. Each of the plurality of power converters is mounted to one of the plurality of movers and is operative to receive power from the secondary winding mounted to the mover and to supply power to the at least one electrical device mounted on the mover.

These and other advantages and features of the invention will become apparent to those skilled in the art from the detailed description and the accompanying drawings. It should be understood, however, that the detailed description and accompanying drawings, while indicating preferred embodiments of the present invention, are given by way of illustration and not of limitation. Many changes and modifications may be made within the scope of the present invention without departing from the spirit thereof, and the invention includes all such modifications.

BRIEF DESCRIPTION OF THE DRAWINGS

Various exemplary embodiments of the subject matter disclosed herein are illustrated in the accompanying drawings in which like reference numerals represent like parts throughout, and in which:

FIG. 1 is an isometric view of an exemplary transport system incorporating multiple movers travelling along a closed curvilinear track according to one embodiment of the present invention;

FIG. 2 is a partial side elevation view of one segment of one embodiment of the transport system of FIG. 1 illustrating activation coils distributed along one surface of the track segment;

FIG. 3 is an isometric view of a mover from the transport system of FIG. 2;

FIG. 4 is a partial sectional view of the transport system of FIG. 1;

FIG. 5 is an exemplary schematic representation of a sliding transformer incorporated into the transport system of FIG. 4;

FIG. 6 is a block diagram representation of the mover illustrated in FIG. 3;

FIG. 7 is a partial top plan view of a track segment illustrating a primary winding for one embodiment of a sliding transformer mounted along the track segment;

FIG. 8 is a partial sectional view of a mover illustrating a secondary winding for the sliding transformer of FIG. 7 mounted along the lower surface of the top member of the mover;

FIG. 9 is a schematic representation of one embodiment of a power converter supplying power to a sliding transformer according to one embodiment of the present invention;

FIG. 10 is a schematic representation of one embodiment of a power converter mounted on the mover to regulate power from a sliding transformer according to one embodiment of the present invention;

FIG. 11 is a partial side elevation view of one segment of another embodiment of the transport system of FIG. 1 illustrating driving magnets distributed along one surface of the track segment;

FIG. 12 is an isometric view of a mover from the transport system of FIG. 11;

FIG. 13 is a block diagram representation of the mover illustrated in FIG. 12;

FIG. 14 is a schematic representation of a motor drive mounted on the mover to regulate power from a sliding transformer to drive coils on the mover according to one embodiment of the invention;

FIG. 15 is a partial sectional view of another embodiment of the transport system;

FIG. 16 is a block diagram representation of one embodiment of the mover illustrated in FIG. 15;

FIG. 17 is a block diagram representation of an embodiment of the mover including motor coils on the mover as used with the transport system illustrated in FIG. 15;

FIG. 18 is a schematic representation of one embodiment of a power converter mounted on the mover to regulate power from a generator mounted on the mover according to one embodiment of the present invention;

FIG. 19 is a partial sectional view of another embodiment of the transport system;

FIG. 20 is a block diagram representation of one embodiment of the mover illustrated in FIG. 19;

5

FIG. 21 is a block diagram representation of an embodiment of the mover including motor coils on the mover as used with the transport system illustrated in FIG. 19; and

FIG. 22 is a schematic representation of one embodiment of a power converter mounted on the mover to regulate power from an optical transmitter according to one embodiment of the present invention.

In describing the various embodiments of the invention which are illustrated in the drawings, specific terminology will be resorted to for the sake of clarity. However, it is not intended that the invention be limited to the specific terms so selected and it is understood that each specific term includes all technical equivalents which operate in a similar manner to accomplish a similar purpose. For example, the word "connected," "attached," or terms similar thereto are often used. They are not limited to direct connection but include connection through other elements where such connection is recognized as being equivalent by those skilled in the art.

DETAILED DESCRIPTION

The various features and advantageous details of the subject matter disclosed herein are explained more fully with reference to the non-limiting embodiments described in detail in the following description.

Turning initially to FIG. 1, an exemplary transport system for moving articles or products includes a track 10 made up of multiple segments 12, 14. According to the illustrated embodiment, the segments define a generally closed loop supporting a set of movers 100 movable along the track 10. The track 10 is oriented in a horizontal plane and supported above the ground by a base 15 extending vertically downward from the track 10. According to the illustrated embodiment, the base 15 includes a pair of generally planar support plates 17, located on opposite sides of the track 10, with mounting feet 19 on each support plate 17 to secure the track 10 to a surface. The illustrated track 10 includes four straight segments 12, with two straight segments 12 located along each side of the track and spaced apart from the other pair. The track 10 also includes four curved segments 14 where a pair of curved segments 14 is located at each end of the track 10 to connect the pairs of straight segments 12. The four straight segments 12 and the four curved segments 14 form a generally oval track and define a closed surface over which each of the movers 100 may travel. It is understood that track segments of various sizes, lengths, and shapes may be connected together to form a track 10 without deviating from the scope of the invention.

For convenience, the horizontal orientation of the track 10 shown in FIG. 1 will be discussed herein. Terms such as upper, lower, inner, and outer will be used with respect to the illustrated track orientation. These terms are relational with respect to the illustrated track and are not intended to be limiting. It is understood that the track may be installed in different orientations, such as sloped or vertical, and include different shaped segments including, but not limited to, straight segments, inward bends, outward bends, up slopes, down slopes and various combinations thereof. Further, each track segment 12, 14 is shown in a generally horizontal orientation. The track segments 12, 14 may also be oriented in a generally vertical orientation and the width of the track 10 may be greater in either the horizontal or vertical direction according to application requirements. The movers 100 will travel along the track and take various orientations according to the configuration of the track 10 and the relationships discussed herein may vary accordingly.

6

Each track segment 12, 14 includes a number of independently attached rails 20 on which each mover 100 runs. According to the illustrated embodiment, rails 20 extend generally along the outer periphery of the track 10. A first rail 20 extends along an upper surface 11 of each segment and a second rail 20 extends along a lower surface 13 of each segment. It is contemplated that each rail 20 may be a singular, molded or extruded member or formed from multiple members. It is also contemplated that the cross section of the rails 20 may be circular, square, rectangular, or any other desired cross-sectional shape without deviating from the scope of the invention. The rails 20 generally conform to the curvature of the track 10 thus extending in a straight path along the straight track segments 12 and in a curved path along the curved track segments 14. The rails 20 may be thin with respect to the width of the track 10 and span only a partial width of the surface of the track 10 on which it is attached. According to the illustrated embodiment, each rail 20 includes a base portion 22 mounted to the track segment and a track portion 24 along which the mover 100 runs. Each mover 100 includes complementary rollers 110 to engage the track portion 24 of the rail 20 for movement along the track 10.

One or more movers 100 are mounted to and movable along the rails 20 on the track 10. With reference next to FIG. 3, an exemplary mover 100 is illustrated. Each mover 100 includes a side member 102, a top member 104, and a bottom member 106. The side member 102 extends for a height at least spanning a distance between the rail 20 on the top surface 11 of the track 10 and the rail 20 on the bottom surface 13 of the track 10 and is oriented generally parallel to a side surface 21 when mounted to the track 10. The top member 104 extends generally orthogonal to the side member 102 at a top end of the side member 102 and extends across the rail 20 on the top surface 11 of the track 10. The top member 104 includes a first segment 103, extending orthogonally from the side member 102 for the width of the rail 20, which is generally the same width as the side member 102. A set of rollers 110 are mounted on the lower side of the first segment 103 and are configured to engage the track portion 24 of the rail 20 mounted to the upper surface 11 of the track segment. According to the illustrated embodiment two pairs of rollers 110 are mounted to the lower side of the first segment 103 with a first pair located along a first edge of the track portion 24 of the rail and a second pair located along a second edge of the track portion 24 of the rail 20. The first and second edges and, therefore, the first and second pairs of rollers 110 are on opposite sides of the rail 20 and positively retain the mover 100 to the rail 20. The bottom member 106 extends generally orthogonal to the side member 102 at a bottom end of the side member 102 and extends for a distance sufficient to receive a third pair of rollers 110 along the bottom of the mover 100. The third pair of rollers 110 engage an outer edge of the track portion 24 of the rail 20 mounted to the lower surface 13 of the track segment. Thus, the mover 100 rides along the rails 20 on the rollers 110 mounted to both the top member 104 and the bottom member 106 of each mover 100. The top member 104 also includes a second segment 120 which protrudes from the first segment 103 an additional distance beyond the rail 20 and is configured to hold a position magnet 130. According to the illustrated embodiment, the second segment 120 of the top member 104 includes a first portion 122 extending generally parallel to the rail 20 and tapering to a smaller width than the first segment 103 of the top member 104. The second segment 120 also includes a second portion 124 extending downward from and generally orthogonal to

the first portion **122**. The second portion **124** extends downward a distance less than the distance to the upper surface **11** of the track segment but of sufficient distance to have the position magnet **130** mounted thereto. According to the illustrated embodiment, a position magnet **130** is mounted within a recess **126** on the second portion **124** and is configured to align with a sensor **150** mounted within the top surface **11** of the track segment.

A linear drive system is incorporated in part on each mover **100** and in part within each track segment **12**, **14** to control motion of each mover **100** along the segment. According to one embodiment of the invention shown in FIG. **2**, the linear drive system includes drive magnets **140** mounted to the side member **102**. According to the illustrated embodiment, the drive magnets **140** are arranged in a block along an inner surface of the side member **102** with separate magnet segments alternately having a north pole, N, and south pole, S, pole facing the track segment **12**. The drive magnets **140** are typically permanent magnets, and two adjacent magnet segments including a north pole and a south pole may be considered a pole-pair. The drive magnets **140** are mounted on the inner surface of the side member **102** and when mounted to the track **10** are spaced apart from a series of coils **50** extending along the track **10**. As shown in FIG. **4**, an air gap **141** is provided between each set of drive magnets **140** and the coils **50** along the track **10**. On the track **10**, the linear drive system includes a series of parallel coils **50** spaced along each track segment **12** as shown in FIG. **2**. According to the illustrated embodiment, each coil **50** is placed in a channel **23** extending longitudinally along one surface of the track segment **12**. The electromagnetic field generated by each coil **50** spans the air gap **141** and interacts with the drive magnets **140** mounted to the mover **100** to control operation of the mover **100**.

According to another embodiment of the invention shown in FIGS. **11-12**, the linear drive system includes drive magnets **255** mounted along the track. With reference also to FIG. **4**, the drive magnets **255** may be mounted in the channel **23** extending longitudinally along one surface of the track segment **12**. A set of drive coils **250** is mounted to each mover **100**. The drive coils **250** are mounted to the side member **102** and spaced apart from the drive magnets **255** such that an air gap **141** is defined between each set of drive coils **250** and the drive magnets **255** along the track. The drive magnets **255** are preferably arranged with consecutive magnet segments alternately having a north pole, N, and south pole, S, pole facing the mover **100**. The mover **100** further includes a motor drive **200** mounted to the side member **102** and, as illustrated, is positioned between the side member **102** and the drive coils **250**. As will be discussed in more detail below, the motor drive **200** receives power from a power source located off the mover **100** and delivers the power to the drive coils **250**. The motor drive **200** controls the voltage and/or current provided to each drive coil **250** such that an electromagnetic field generated by each drive coil **250** on the mover **100** interacts with the drive magnets **255** mounted along the track **10** to control motion of the mover **100** along the track. Mounting the motor drive **200** along the side member **102** allows the side member to serve as a heat sink for the motor drive **200**. However, it is contemplated that the motor drive **200** may be mounted in other locations on the mover **100** without deviating from the scope of the invention.

According to one embodiment of the invention, a sliding transformer is provided to transfer power between the track and each mover. The sliding transformer includes a primary winding extending along the track and a secondary winding

mounted to each mover. The primary winding may be a single coil or multiple coils. If formed as a single coil, the primary winding may include a pair of bus bars extending along the track where one bus bar defines a forward conduction path and the other bus bar defines a return conduction path. If the primary winding is formed of multiple coils, a conductor may be wound along the track in the direction of travel to define the forward and reverse conduction paths or, optionally, multiple traces on a printed circuit board may be formed. It is contemplated that the primary winding may be formed of a number of closed loops extending along a portion of the track. The track, for example, may include multiple track segments and a single primary winding may extend along the surface of each track segment. The secondary winding may similarly be a single coil or multiple coils. If formed as a single coil, the secondary winding may include a pair of bus bars extending along the mover in the direction of travel where one bus bar defines a forward conduction path and the other bus bar defines a return conduction path. If the secondary winding is formed of multiple coils, a conductor may be wound along the mover in the direction of travel to define the forward and reverse conduction paths or, optionally, multiple traces on a printed circuit board may be formed. Each mover includes a single secondary winding and multiple movers travel along the track. The primary and secondary windings are generally aligned with each other and extend along the track and along the mover in the direction of travel with an air gap present between the windings.

Turning to FIGS. **4** and **5**, a sliding transformer **170** providing power to the mover **100** from a power source located off the mover is illustrated. The sliding transformer **170** provides wireless power transfer between the track **10** and a mover **100**. According to the illustrated embodiment, a primary winding **172** is provided on the track **10** and a secondary winding **182** is provided on the mover **100**. The primary winding **172** includes a forward conduction path **173** and a reverse conduction path **175** extending longitudinally along the track **10**. According to one embodiment of the invention, the forward and reverse conduction paths **173**, **175** may span multiple track segments **12**, **14**. An electrical connector may be provided between track segments **12**, **14** to establish a continuous electrical connection between segments **12**, **14**. In certain applications, such as a short oval, a single primary winding may be provided. One end for each of the forward and reverse conduction paths is connected to a power source and the other end for each of the forward and reverse conduction paths is electrical connected to each other to establish a conductive loop. In other applications, for example, due to an extended track length, it may be desirable to provide multiple primary windings **172**, where each primary winding extends for a portion of the length of the track **10**. According to one embodiment of the invention, each track segment **12**, **14** includes a separate primary winding **172** extending the length of the track segment.

The forward and reverse conduction paths **173**, **175** for the primary winding **172** may include either a single conductor or multiple conductors. With reference to FIG. **5**, a first bus bar **174** is provided in the forward conduction path **173** and a second bus bar **176** is provided in the reverse conduction path **175**. If a separate primary winding **172** is present on each track segment, one end of each bus bar **174**, **176** is connected to a power source and the other end of each bus bar may include an end cap joining the two bus bars and establishing a conductive loop. If the primary winding **172** spans multiple track segments, then an electrical connector may be provided between track segments to join adjacent

bus bars. With reference to FIG. 7, the primary winding 172 may also include multiple conductors in each of the forward and reverse conduction paths 173, 175. According to one embodiment of the invention, a single conductor may be wound along the length of the track segment 12 to form a coil. According to another embodiment of the invention, a printed circuit board (PCB) may be mounted along the length of the track segment 12 and a number of traces may be defined along the PCB to define the coil. In either embodiment, a first portion of the conductors define the forward conduction path 173 and a second portion of the conductors define the reverse conduction path 175.

The secondary winding 182 includes a forward conduction path 183 and a reverse conduction path 185 extending in the direction of motion of the mover 100. It is contemplated that each mover 100 will include a single secondary winding 182. However, in some embodiments, multiple secondary windings 182 may be mounted on a mover 100 with each secondary winding 182 receiving power from the primary winding 172. One end for each of the forward and reverse conduction paths is electrically connected to each other to establish a conductive loop and the other end supplies power to an electrical load on the mover 100. It is contemplated that the electrical load may be an electrical device 300 such as an actuator or a sensor, which may be energized by either an alternating current (AC) voltage or a direct current (DC) voltage. A power converter 260 is provided to regulate the power flow received from the secondary winding 182 to the electrical load.

The forward and reverse conduction paths 183, 185 for the secondary winding 182 may include either a single conductor or multiple conductors. With reference to FIG. 5, a first bus bar 184 is provided in the forward conduction path 183 and a second bus bar 186 is provided in the reverse conduction path 185. One end of each bus bar 184, 186 is connected to the electrical load on the mover 100 and the other end of each bus bar may include an end cap joining the two bus bars and establishing a conductive loop. With reference to FIG. 8, the secondary winding 182 may also include multiple conductors in each of the forward and reverse conduction paths 183, 185. According to one embodiment of the invention, a single conductor may be wound along the mover 100 in the direction of travel of the mover 100 to form a coil. According to another embodiment of the invention, a printed circuit board (PCB) may be mounted to the mover 100 and a number of traces may be defined along the PCB to define the coil. In either embodiment, a first portion of the conductors define the forward conduction path 183 and a second portion of the conductors define the reverse conduction path 185.

Turning next to FIG. 9, an exemplary power converter 350 for supplying power to the primary winding 172 is illustrated. The power converter 350 is configured to receive a three-phase AC voltage 352 at an input 354 of the power converter. The three-phase AC voltage 352 is, in turn, provided to a rectifier section 356 of the power converter 350. The rectifier section 356 may include any electronic device suitable for passive or active rectification as is understood in the art. According to the illustrated embodiment, the rectifier section 356 includes a set of diodes 358 forming a diode bridge that rectifies the three-phase AC voltage to a DC voltage on the DC bus 362. Optionally, the rectifier section 356 may include other solid-state devices including, but not limited to, thyristors, silicon controlled rectifiers (SCRs), or transistors to convert the input voltage 352 to a DC voltage for the DC bus 362. The DC voltage is present between a positive rail 364 and a negative rail 366

of the DC bus 362. A DC bus capacitor 368 is connected between the positive and negative rails, 364 and 366, to reduce the magnitude of the ripple voltage resulting from converting the AC voltage to a DC voltage. It is understood that the DC bus capacitor 368 may be a single capacitor or multiple capacitors connected in parallel, in series, or a combination thereof. The magnitude of the DC voltage between the positive and negative rails, 364 and 366, is generally equal to the magnitude of the peak of the AC input voltage.

The DC bus 362 is connected in series between the rectifier section 356 and an inverter section 370. The inverter section 370 consists of a number of switches 372. Each switch 372 is preferably a solid-state switching element, such as a transistor, thyristor, or SCR as is known in the art. The switching element may also include a free-wheeling diode connected across the switching element. Each of the switches 372 receives a switching signal, sometimes referred to as a gating signal, 374 to selectively enable the switch 372 and to convert the DC voltage from the DC bus 362 into a controlled AC voltage at an output 376 of the inverter section 370. When enabled, each switch 372 connects the respective rail 364, 366 of the DC bus 362 to an output terminal. The primary winding 172 is connected to the output 376 of the inverter section to receive the controlled AC voltage as a power source for transmitting power from the track 10 to the movers 100.

One or more modules are used to control operation of the power converter 350. The modules may be stored programs executed on one or more processors, logic circuits, or a combination thereof. According to the illustrated embodiment, the power converter 350 includes a controller 351 and a memory device 353 in communication with the controller 351. The controller 351 may be implemented, for example, in a microprocessor, application specific integrated circuit (ASIC), field programmable gate array (FPGA), or other such customizable device. The memory device 353 may include transitory memory, non-transitory memory or a combination thereof. The memory device 353 may be configured to store data and programs, which include a series of instructions executable by the controller 351. It is contemplated that the memory device 353 may be a single device, multiple devices, or incorporated, for example, as a portion of another device such as an application specific integrated circuit (ASIC). The controller 351 is in communication with the memory 353 to read the instructions and data as required to control operation of the power converter 350.

The controller 351 also receives feedback signals indicating the current operation of the power converter 350. The power converter 350 may include a voltage sensor 380 and/or a current sensor 382 on the DC bus 362 generating a feedback signal corresponding to the magnitude of voltage and/or current present on the DC bus 362. The power converter 350 may also include a voltage sensor 384 and/or a current sensor 386 generating a feedback signal corresponding to the magnitude of voltage and/or current present at the output 376 of the inverter section 370. The controller 351 utilizes the feedback signals to generate the switching signals 374 to control operation of the inverter section 370 and to generate an output voltage having a desired magnitude and frequency for the primary winding 172.

It is contemplated that impedance matching circuits may be provided on one or both sides of the sliding transformer. A first impedance matching circuit 177 is illustrated between the utility power supply 171 and the primary winding 172, and a second impedance matching circuit 187 is illustrated between the secondary winding 182 and the power converter

260. The impedance matching circuit 177 may include one or more reactive components, such as an inductor and/or a capacitor, and resistors may be connected in series or parallel to create a resonant circuit. The frequency of the resonant circuit is selected to amplify a magnitude of voltage and/or current present on the windings to maximize power transfer across the sliding transformer.

With reference also to FIG. 6, the secondary winding 182 is spaced apart from the primary winding 172 by an air gap 180. The current conducted in the primary winding 172 establishes an electromagnetic field along the forward and reverse conduction paths 173, 175. The forward and reverse conduction paths 183, 185 of the secondary winding 182 are generally aligned with the forward and reverse conduction paths 173, 175 of the primary winding 172 and separated by the air gap 180. In order for a current to be induced within the secondary winding 182 by the electromagnetic field generated by the primary winding 172, the secondary winding 182 must be located within the field. Thus, the air gap 180 is small and may be, for example, less than 1.5 millimeters wide and, preferably, is less than 0.75 millimeters wide. In one embodiment of the invention, it is contemplated that the air gap 180 is about 0.5 millimeters wide.

Referring again to FIG. 9, the illustrated mover includes a rectifier section 262 with a set of diodes 264 to convert the AC voltage induced in the secondary winding 182 to a DC voltage present on a DC bus 261. A DC bus capacitor 266 is connected between the positive and negative rails, 263 and 265, to reduce the magnitude of the ripple voltage resulting from converting the AC voltage to a DC voltage. An electrical load 300 may be applied to the DC bus 261. The power converter 350 on the track 10 is configured to regulate the voltage and/or current supplied to the primary winding 172 to, in turn, provide a desired power level to the electrical load 300.

According to another embodiment of the invention, shown in FIG. 10, the mover 100 may also include a power converter 260 to regulate power flow on the mover 100. The power converter 260 is configured to receive the AC voltage from the secondary winding 182 at an input 259 of the power converter. It is contemplated that impedance matching circuits may be provided on one or both sides of the sliding transformer. A first impedance matching circuit 177 is illustrated between the utility power supply 171 and the primary winding 172, and a second impedance matching circuit 187 is illustrated between the secondary winding 182 and the power converter 260. The AC voltage from either the secondary winding 182 or the impedance matching circuit 187, if provided, is, in turn, provided to a rectifier section 262 of the power converter 260. The rectifier section 262 may include any electronic device suitable for passive or active rectification as is understood in the art. According to the illustrated embodiment, the rectifier section 262 includes a set of diodes 264 forming a diode bridge that rectifies the AC voltage to a DC voltage on the DC bus 261. Optionally, the rectifier section 262 may include other solid-state devices including, but not limited to, thyristors, silicon controlled rectifiers (SCRs), or transistors to convert the input voltage to a DC voltage for the DC bus 261. The DC voltage is present between a positive rail 263 and a negative rail 265 of the DC bus 261. A DC bus capacitor 266 is connected between the positive and negative rails, 263 and 265, to reduce the magnitude of the ripple voltage resulting from converting the AC voltage to a DC voltage. It is understood that the DC bus capacitor 266 may be a single capacitor or multiple capacitors connected in parallel, in series, or a combination thereof. The magnitude of the DC

voltage between the positive and negative rails, 263 and 265, is generally equal to the magnitude of the peak of the AC input voltage.

The DC bus 261 is connected in series between the rectifier section 262 and a switching section 270. It is contemplated that the switching section 270 may be configured to provide either an AC voltage output or a DC voltage output. The DC voltage output may be at a different voltage potential than the DC voltage potential present on the DC bus 261. According to the illustrated embodiment, the switching section 270 is arranged as an inverter to provide an AC voltage output. The switching section 270 consists of a number of switches 272. Each switch 272 is preferably a solid-state switching element, such as a transistor, thyristor, or SCR as is known in the art. The switching element may also include a free-wheeling diode connected across the switching element. Each of the switches 272 receives a switching signal, sometimes referred to as a gating signal, 274 to selectively enable the switch 272 and to convert the DC voltage from the DC bus 261 into a controlled AC voltage at an output 276 of the switching section 270. When enabled, each switch 272 connects the respective rail 263, 265 of the DC bus 261 to an output terminal. One or more electrical loads 300 are connected to the output 276 of the inverter section to receive the controlled AC voltage as a power source to enable operation of the device on the mover 100.

One or more modules are used to control operation of the power converter 260. The modules may be stored programs executed on one or more processors, logic circuits, or a combination thereof. According to the illustrated embodiment, the power converter 260 includes a controller 271 and a memory device 273 in communication with the controller 271. The controller 271 may be implemented, for example, in a microprocessor, application specific integrated circuit (ASIC), field programmable gate array (FPGA), or other such customizable device. The memory device 273 may include transitory memory, non-transitory memory or a combination thereof. The memory device 273 may be configured to store data and programs, which include a series of instructions executable by the controller 271. It is contemplated that the memory device 273 may be a single device, multiple devices, or incorporated, for example, as a portion of another device such as an application specific integrated circuit (ASIC). The controller 271 is in communication with the memory 273 to read the instructions and data as required to control operation of the power converter 260.

The power converter 260 also receives feedback signals indicating the current operation of the power converter 260. The power converter 260 may include a voltage sensor 280 and/or a current sensor 282 on the DC bus 261 generating a feedback signal corresponding to the magnitude of voltage and/or current present on the DC bus 261. The power converter 260 may also include a voltage sensor 284 and/or a current sensor 286 generating a feedback signal corresponding to the magnitude of voltage and/or current present at the output 276 of the switching section 270. The controller 271 utilizes the feedback signals to generate the switching signals 274 to control operation of the switching section 270 and to generate a desired output voltage for the load 300 present on the mover 100.

Turning next to FIGS. 15-18, a generator 402 may be mounted to the mover 100 to provide power for use on the mover 100. The generator 402 includes a drive shaft 404 connected to a drive wheel 406. The drive wheel 406 may be, for example, a friction wheel, aligned with a side of a rail 20 or with a side surface 21 of the track segment 12. As the

mover **100** is commanded to travel along the track, the drive wheel **406** engages the side of the rail **20**, causing the drive wheel **406** to turn. The drive wheel **406**, in turn, rotates the drive shaft **404** causing a rotor within the generator to turn. As would be understood by one skilled in the art, rotation of the rotor generates power at an output of the generator due, for example, to rotation of permanent magnets mounted to the rotor, generating a magnetic field within the generator that induces a voltage and/or current on a stator coil within the generator. A cable **408** connects the output of the generator to a power converter **410** mounted on the mover **100**.

The power converter **410**, as shown in more detail in FIG. **18**, may be configured to receive an AC voltage from the generator **402** and convert the AC voltage to a desired AC or DC voltage for use by an electronic device on the mover **100**. The illustrated power converter **410** receives the AC voltage from the generator **402** at an input **424** of the power converter. The AC voltage is, in turn, provided to a rectifier section **426** of the power converter **410**. The rectifier section **426** may include any electronic device suitable for passive or active rectification as is understood in the art. According to the illustrated embodiment, the rectifier section **426** includes a set of diodes **428** forming a diode bridge that rectifies the three-phase AC voltage to a DC voltage on the DC bus **432**. Optionally, the rectifier section **426** may include other solid-state devices including, but not limited to, thyristors, silicon controlled rectifiers (SCRs), or transistors to convert the input voltage to a DC voltage for the DC bus **432**. The DC voltage is present between a positive rail **436** and a negative rail **436** of the DC bus **432**. A DC bus capacitor **438** is connected between the positive and negative rails, **434** and **436**, to reduce the magnitude of the ripple voltage resulting from converting the AC voltage to a DC voltage. It is understood that the DC bus capacitor **438** may be a single capacitor or multiple capacitors connected in parallel, in series, or a combination thereof. The magnitude of the DC voltage between the positive and negative rails, **434** and **436**, is generally equal to the magnitude of the peak of the AC input voltage.

According to the illustrated embodiment, the DC bus **432** is connected in series between the rectifier section **426** and an inverter section **441**). The inverter section **440** consists of a number of switches **442**. Each switch **442** is preferably a solid-state switching element, such as a transistor, thyristor, or SCR as is known in the art. The switching element may also include a free-wheeling diode connected across the switching element. Each of the switches **442** receives a switching signal, sometimes referred to as a gating signal, **444** to selectively enable the switch **442** and to convert the DC voltage from the DC bus **432** into a controlled AC voltage at an output **446** of the inverter section. **440**. When enabled, each switch **442** connects the respective rail **434**, **436** of the DC bus **432** to an output terminal. The AC voltage present at the output **446** of the power converter **410** may be supplied to and provide power for AC electrical devices **300** present on the mover **100**.

Optionally, the power converter **410** may be configured to supply a DC voltage to an electrical device **300** on the mover. Rather than having an inverter section **440** as shown in FIG. **18**, the power converter may include a DC-to-DC power converter that converts the voltage present on the DC bus **432** to another DC voltage suitable for powering the DC electrical device **300**. Optionally, the AC voltage from the generator **402** may be converted directly to the desired DC voltage desired to power a DC electrical device **300** and the device **300** may be connected directly to the DC bus **432**. As

further illustrated in FIG. **18**, an energy storage device **418** such as a battery or a super-capacitor may be mounted to the mover **100**. An energy regulator **415** may be provided to charge the energy storage device **418** when excess electrical energy is being generated by the generator **402**, and the energy regulator **415** may supply the stored energy from the energy storage device **418** to the DC bus **432** when the energy demanded from the electrical devices **300** exceed the energy being generated by the generator **402**. It is further contemplated that the energy regulator **415** may be incorporated within the power converter **410** such that the controller **421** for the power converter **410** also controls the energy regulator **415**.

One or more modules are used to control operation of the power converter **410**. The modules may be stored programs executed on one or more processors, logic circuits, or a combination thereof. According to the illustrated embodiment, the power converter **410** includes a controller **421** and a memory device **423** in communication with the controller **421**. The controller **421** may be implemented, for example, in a microprocessor, application specific integrated circuit (ASIC), field programmable gate array (FPGA), or other such customizable device. The memory device **423** may include transitory memory, non-transitory memory or a combination thereof. The memory device **423** may be configured to store data and programs, which include a series of instructions executable by the controller **421**. It is contemplated that the memory device **423** may be a single device, multiple devices, or incorporated, for example, as a portion of another device such as an application specific integrated circuit (ASIC). The controller **421** is in communication with the memory **423** to read the instructions and data as required to control operation of the power converter **410**.

The controller **421** also receives feedback signals indicating the current operation of the power converter **410**. The power converter **410** may include a voltage sensor **450** and/or a current sensor **452** on the DC bus **432** generating a feedback signal corresponding to the magnitude of voltage and/or current present on the DC bus **432**. The power converter **410** may also include a voltage sensor **454** and/or a current sensor **456** generating a feedback signal corresponding to the magnitude of voltage and/or current present at the output **446** of the inverter section **440**. The controller **421** utilizes the feedback signals to generate the switching signals **444** to control operation of the inverter section **440** and to generate an output voltage having a desired magnitude and frequency for the electrical devices **300** present on the mover **100**.

With reference again to FIG. **15**, the power converter **410** is illustrated as mounted on a circuit board **412** and stand-offs **414** on the upper surface of the mover **100**. An energy storage device **418** is similarly mounted to the upper surface of the mover **100** and connected to the power converter **410** via a cable **416**. The illustrated embodiment further includes a platform **420** mounted to the top surface of the mover **100** with stand-offs **422**. The platform **420** may be configured, for example, to receive a work piece, additional fixtures, or the electronic devices **300** to be powered by the generator **402**. The illustrated embodiment is intended to be exemplary and is not intended to be limiting. An alternate embodiment, for example, may include an enclosed module which includes the power converter **410** and/or the energy storage device **418**. The enclosed module may be mounted to the top, side, or bottom of the mover **100**.

Turning next to FIGS. **19-22**, an optical transmitter **505** may be mounted to the track and be configured to transmit power to the mover **100** via a light beam **508**. According to

15

the illustrated embodiment, a mounting fixture **501** extends down below the track segment **12** and is configured to receive the light from the optical transmitter **505**. The optical transmitter **505** may be, for example, one or more laser diodes **504** mounted within a housing **503** which is, in turn attached to the mounting fixture **501**. As shown in FIG. **22**, the optical transmitter **505** may receive power from a utility supply **171**. The AC voltage from the utility may be converted to a DC voltage with a rectifier circuit **500**. It is contemplated that the utility voltage may be provided to each track segment **12** with separate rectifier circuits **500** similarly mounted on each track segment **12**. Optionally, one or more front-end rectifier units may receive the utility voltage and supply a DC voltage to the track or a portion of the track, and each track segment **12** receives the DC voltage from the front-end rectifier unit. Each rectifier circuit **500** or front-end rectifier unit may include any electronic device suitable for passive or active rectification as is understood in the art. According to the illustrated embodiment, the rectifier circuit **500** includes a set of diodes forming a diode bridge that rectifies the AC voltage from the utility supply **171** to a DC voltage for the driver circuit **502**. Optionally, the rectifier circuit **500** may include other solid-state devices including, but not limited to, thyristors, silicon controlled rectifiers (SCRs), or transistors to convert the input voltage to a DC voltage. The DC voltage is provided to a driver circuit **502**, which, in turn, enables one or more laser diodes **504**. Optionally, the driver circuit **502** may receive an AC voltage directly and incorporate a rectifier circuit or other power conversion circuit to supply a DC voltage to the laser diode **504**. Although illustrated as a single laser diode **504**, it is contemplated that multiple laser diodes **504** may be utilized. The optical transmitter **505** may also include one or more optical devices, such as filters, lenses, and the like to direct and focus the light emitted from each laser diode **504** toward a receiver mounted on the mover **100**.

The receiver **510** on the mover **100** includes one or more devices that convert light energy into electrical energy. According to the illustrated embodiment, the receiver **510** includes one or more photovoltaic modules and may form a photovoltaic array. Light incident on the photovoltaic array **510** is converted into electrical energy. Because the frequency of the light emitted from the optical transmitter **505** may be selected and/or is known, the construction of the photovoltaic array **510** may be selected to improve the efficiency of energy conversion between optical energy and electrical energy.

A power converter **520**, as shown in more detail in FIG. **22**, may be configured to receive a DC voltage from the PV array **510** and convert the input DC voltage to either an AC voltage or a DC voltage of another amplitude for use by an electronic device on the mover **100**. The illustrated power converter **520** receives the DC voltage from the PV array **510** at an input **522** to the power converter **520**. The DC voltage is, in turn, provided to a voltage regulator **524**. As is understood, a PV array **510** typically outputs a DC voltage. The amplitude of the DC voltage may be different than an amplitude of a DC voltage needed to operate an electrical device **300** on the mover **100**. Similarly, the amplitude of the DC voltage may be different than an amplitude of a DC voltage needed to supply an AC voltage to an electrical device **300** on the mover **100**. The voltage regulator **524** may be configured as a buck converter or a boost converter to change the voltage level from a first amplitude supplied by the PV array **510** to a second amplitude required by other devices mounted on the mover **100**. The voltage regulator **524** may further include devices, such as capacitors and the

16

like to reduce voltage ripple due to changes in the amount of light incident on the PV array **510** and to help maintain the voltage level at a desired voltage level. The DC voltage output from the voltage regulator is present between a positive rail **528** and a negative rail **530** of a DC bus **526**. A DC bus capacitor **532** is shown connected between the positive and negative rails, **528** and **530**, to reduce the magnitude of the ripple voltage present on the DC bus **526**. As previously indicated, it is contemplated that the DC bus capacitor **532** may be incorporated into the voltage regulator **425** and/or in the inverter section **534**.

According to the illustrated embodiment, the DC bus **526** is connected in series between the voltage regulator **524** and an inverter section **534**. The inverter section **534** is used to provide an AC voltage to electrical devices **300** mounted on the mover **100**. The inverter section **534** may consist of a number of switches, as discussed above in other inverter sections. Each switch is preferably a solid-state switching element, such as a transistor, thyristor, or SCR as is known in the art. The switching element may also include a free-wheeling diode connected across the switching element. Each of the switches receives a switching signal, sometimes referred to as a gating signal, to selectively enable the switch and to convert the DC voltage from the DC bus **526** into a controlled AC voltage at an output **536** of the inverter section **534**. The AC voltage present at the output **536** of the power converter **520** may be supplied to and provide power for AC electrical devices **300** present on the mover **100**.

Optionally, the power converter **520** may be configured to supply a DC voltage to an electrical device **300** on the mover. Each DC electrical device **300** may be connected directly to the DC bus **526**. Optionally, a separate DC-to-DC power converter may be provided to convert the voltage present on the DC bus **526** to another DC voltage suitable for powering the DC electrical device **300**. According to still another embodiment, the voltage regulator **524** may be configured to output multiple DC voltages including, for example, positive or negative five volts (+/- 5 VDC) or positive or negative twenty-four volts (+/- 24 VDC).

As further illustrated in FIG. **19**, an energy storage device **518** such as a battery or a super-capacitor may be mounted to the mover **100**. The energy storage device **518** may include a dedicated energy regulator to charge the energy storage device **518** when excess electrical energy is being generated by the photovoltaic array **510** and to draw the stored energy from the energy storage device **518** to the DC bus **526** when the energy demanded from the electrical devices **300** exceed the energy being generated by the photovoltaic array **510**. Optionally, the energy storage device **518** may be connected directly to the DC bus **526**. It is further contemplated that an energy regulator for the energy storage device **518** may be incorporated within the voltage regulator **524** such that the controller **533** for the power converter **520** also controls the energy regulator.

One or more modules are used to control operation of the power converter **520**. The modules may be stored programs executed on one or more processors, logic circuits, or a combination thereof. According to the illustrated embodiment, the power converter **520** includes a controller **533** and a memory device **531** in communication with the controller **533**. The controller **533** may be implemented, for example, in a microprocessor, application specific integrated circuit (ASIC), field programmable gate array (FPGA), or other such customizable device. The memory device **531** may include transitory memory, non-transitory memory or a combination thereof. The memory device **531** may be con-

figured to store data and programs, which include a series of instructions executable by the controller 533. It is contemplated that the memory device 531 may be a single device, multiple devices, or incorporated, for example, as a portion of another device such as an application specific integrated circuit (ASIC). The controller 533 is in communication with the memory 531 to read the instructions and data as required to control operation of the power converter 520.

The controller 533 also receives feedback signals indicating the current operation of the power converter 520. The power converter 520 may include a voltage sensor 540 and/or a current sensor 542 on the DC bus 526 generating a feedback signal corresponding to the magnitude of voltage and/or current present on the DC bus 526. The power converter 520 may also include a voltage sensor 544 and/or a current sensor 546 generating a feedback signal corresponding to the magnitude of voltage and/or current present at the output 536 of the inverter section 534. The controller 533 utilizes the feedback signals to generate the switching signals to control operation of the inverter section 534 and to generate an output voltage having a desired magnitude and frequency for the electrical devices 300 present on the mover 100. The controller 533 may additionally receive additional feedback signals from the voltage regulator 524 and may utilize the feedback signals to regulate the voltage level on the DC bus 526 and/or to supply various levels of DC voltage for use by the electrical devices 300 present on the mover 100.

With reference again to FIG. 19, the power converter 520 is illustrated as mounted on a circuit board 514 and stand-offs 516 on the upper surface of the mover 100. An energy storage device 518 is similarly mounted to the upper surface of the mover 100 and connected to the power converter 520 via a cable 517. The illustrated embodiment further includes a platform 490 mounted to the top surface of the mover 100 with stand-offs 492. The platform 490 may be configured, for example, to receive a work piece, additional fixtures, or the electronic devices 300 to be powered by the optical source 505. The illustrated embodiment is intended to be exemplary and is not intended to be limiting. An alternate embodiment, for example, may include an enclosed module which includes the power converter 520 and/or the energy storage device 518. The enclosed module may be mounted to the top, side, or bottom of the mover 100.

As previously indicated, one embodiment of the linear drive system includes drive magnets 255 arranged along the track 10 and drive coils 250 mounted to each mover. With reference then to FIGS. 11-14, one arrangement of a controller for this embodiment of the linear drive system is illustrated. A sliding transformer is provided between the track 10 and each mover 100 in the manner discussed above. Optionally, other methods of providing power to the mover 100 as it travels along the track may be utilized. The power may be supplied by the generator 402 mounted to the mover 100, as shown in FIG. 17, or by the optical source 505, as shown in FIG. 21. The power sources may further include an energy storage device (e.g., 418 or 518) to supplement power when the power source is not supplying power or not supplying sufficient power to energize the drive coils. Each mover 100 further includes a motor drive 200 configured to receive power from power source on the mover 100, such as the secondary winding 182, the generator 402, or the optical source 505.

With reference to FIG. 14, the motor drive 200 may be configured to receive an AC voltage from the secondary winding 182 at an input 202 of the motor drive. The AC voltage is, in turn, provided to a rectifier section 204 of the

motor drive 200. The rectifier section 204 may include any electronic device suitable for passive or active rectification as is understood in the art. According to the illustrated embodiment, the rectifier section 204 includes a set of diodes 206 forming a diode bridge that rectifies the three-phase AC voltage to a DC voltage on the DC bus 208. Optionally, the rectifier section 204 may include other solid-state devices including, but not limited to, thyristors, silicon controlled rectifiers (SCRs), or transistors to convert the input voltage to a DC voltage for the DC bus 208. The DC voltage is present between a positive rail 210 and a negative rail 212 of the DC bus 208. A DC bus capacitor 214 is connected between the positive and negative rails, 210 and 212, to reduce the magnitude of the ripple voltage resulting from converting the AC voltage to a DC voltage. It is understood that the DC bus capacitor 214 may be a single capacitor or multiple capacitors connected in parallel, in series, or a combination thereof. The magnitude of the DC voltage between the positive and negative rails, 210 and 212, is generally equal to the magnitude of the peak of the AC input voltage.

Optionally, the AC voltage may be supplied to the input of the motor drive 200 from the generator 402. When the mover 100 is travelling, the generator 402 may be configured to generate sufficient energy to propel the mover along the track. In addition, a portion of the energy produced by the generator 402 may be stored in the energy storage device 418. It is contemplated that the power converter 410 shown in FIG. 17 may be a separate power converter from the motor drive 200 or incorporated with the motor drive 200. The AC voltage output from the generator 402, for example may be supplied to a common DC bus, where the common DC bus acts as the DC bus in both the motor drive 200 and the power converter 410. Further, the energy storage device 418 may be connected directly to the shared DC bus as well with the regulator 415 connected between the shared DC bus and the energy storage device 418. The level of charge on the energy storage device is preferably maintained at a sufficient level to supply power to the motor drive 200 to start motion of the mover 100. Subs

According to still another embodiment, the motor drive 200 may be powered directly from the DC bus 526 of the power converter 520 configured to receive power from the optical source 505. It is contemplated that the power converter 520 discussed above with respect to the optical source 505 may be combined with or replace the motor drive 200. The power supplied by the optical source 505 may be utilized directly to energize motor coils 250. Optionally, a common DC bus may be utilized by both the motor drive 200 and the power converter 520, where the inverter section 220 of the motor drive 200 supplies power to the drive coils 250 and the inverter section 534 of the power converter 520 supplies power to AC electronic devices 300 mounted to the mover 100.

The DC, bus 208 is connected in series between the rectifier section 204 and an inverter section 220. The inverter section 220 consists of a number of switches 222. Each switch 222 is preferably a solid-state switching element, such as a transistor, thyristor, or SCR as is known in the art. The switching element may also include a free-wheeling diode connected across the switching element. Each of the switches 222 receives a switching signal, sometimes referred to as a gating signal, 224 to selectively enable the switch 222 and to convert the DC voltage from the DC bus 208 into a controlled AC voltage at an output 226 of the inverter section 220. When enabled, each switch 222 connects the respective rail 210, 212 of the DC bus 208 to an

output terminal. The drive coils **250** are connected to the output **226** of the inverter section to receive the controlled AC voltage to establish an electromagnetic field to interact with the drive magnets **255** and control motion of the corresponding mover **100**.

One or more modules are used to control operation of the motor drive **200**. The modules may be stored programs executed on one or more processors, logic circuits, or a combination thereof. According to the illustrated embodiment, the motor drive **200** includes a controller **230** and a memory device **232** in communication with the controller **230**. The controller **230** may be implemented, for example, in a microprocessor, application specific integrated circuit (ASIC), field programmable gate array (FPGA), other such customizable device. The memory device **232** may include transitory memory, non-transitory memory or a combination thereof. The memory device **232** may be configured to store data and programs, which include a series of instructions executable by the controller **230**. It is contemplated that the memory device **232** may be a single device, multiple devices, or incorporated, for example, as a portion of another device such as an application specific integrated circuit (ASIC). The controller **230** is in communication with the memory **232** to read the instructions and data as required to control operation of the motor drive **200**.

The motor drive **200** also receives feedback signals indicating the current operation of the motor drive **200**. The motor drive **200** may include a voltage sensor **236** and/or a current sensor **238** on the DC bus **208** generating a feedback signal corresponding to the magnitude of voltage and/or current present on the DC bus **208**. The motor drive **200** may also include a voltage sensor **240** and/or a current sensor **242** generating a feedback signal corresponding to the magnitude of voltage and/or current present at the output **226** of the inverter section **220**. The controller **230** utilizes the feedback signals to generate the switching signals **224** to control operation of the inverter section **220** and to generate a desired output voltage for each drive coil **250** present on the mover **100**.

It is further contemplated that a mover **100** with a motor drive **200** may also include one or more electronic devices mounted to the mover **100**. As illustrated, a load **300** is powered by a power converter **260**, separate from the motor drive **200**, also mounted to the mover **100**. The illustrated power converter **260** includes only a switching section **270** as described above with respect to FIG. **10**. The DC bus of the power converter **260** illustrated in FIG. **14** is connected directly to the DC bus **208** of the motor drive **200**. Optionally, the power converter **260** may include an input receiving power from the source in parallel with the motor drive **200**.

In operation, a power source provides power to each mover **100** travelling along the track **10** without requiring a fixed connection to the mover **100**. According to one embodiment of the invention, the sliding transformer wirelessly provides power from the track **10** to each mover **100** travelling along the track **10**. According to the embodiment illustrated in FIG. **10**, a utility power supply **171** is connected to the primary winding **172**. The utility power supply **171** provides power at a fixed voltage and frequency and the power converter **260** on each mover **100** regulates power drawn from the secondary winding **182**. Optionally, a power converter **350** may be connected between a utility power supply and the primary winding **172**, as shown in FIG. **9**. The power converter **350** may be controlled to provide a voltage to the primary winding **172** with a variable voltage and/or a variable frequency. If the primary winding **172** spans multiple track segments, a single connection to the

power supply is provided for each primary winding and suitable connectors are provided between segments to join the forward and reverse conduction paths. If a separate primary winding **172** is provided for each track segment **12**, a separate power converter **350** may be provided on each track segment to convert power from an input power source to a modulated voltage for the primary winding **172**.

At a fixed voltage level, for example, 110 VAC, the frequency of the voltage applied to the primary winding **172** impacts the amount of power transferred between the primary and secondary windings and also impacts the level of voltage ripple present at the secondary winding. With a utility power supply **171**, voltage is provided, for example, at 110 VAC and 60 Hz. With a power converter **350** supplying power to the primary winding **172**, the output may be modulated to provide voltage at a higher frequency, ranging, for example, from 60-2000 Hz. According to one embodiment of the invention, the voltage is provided with a frequency in a range of 250-1000 Hz.

Increasing the frequency of the voltage supplied to the primary winding, impacts voltage coupling between the primary winding **172** and the secondary winding **182**. As the frequency of the voltage increases, the ripple on the voltage present on the secondary winding **182** decreases. As a result, the capacitance value for the DC bus capacitor **266** present on the mover **100** can be decreased. However, as the frequency increases, the amplitude of the voltage present on the secondary winding decreases and, therefore, the total power transferred similarly decreases. A comparison of the voltages and power present on the secondary winding of an exemplary sliding transformer is presented in Table 1 below. The amplitude of input voltage is constant at 110 VAC and the number of turns on the secondary winding is constant at sixty turns.

TABLE 1

Evaluation of different frequencies of voltage provided to a primary winding with a secondary winding having 60 turns			
	Frequency		
	60 Hz	250 Hz	1000 Hz
V_{avg} (V)	80	79	62
V_{ripple} (V_{pk-pk})	30	6	1
P_{avg} (W)	713	629	386

The power transferred between the primary winding **172** and the secondary winding **182** is further influenced by the number of turns present in the secondary winding. According to one embodiment of the invention, the number of turns present in the primary winding matches the number of turns present in the secondary winding to provide a 1:1 turns ratio. It is contemplated that various other turns ratios may be utilized without deviating from the scope of the invention. As the number of turns in the secondary winding **182** increases, the voltage level on the secondary winding decreases. However, as the number of turns in the secondary winding **182** increases, the magnitude of voltage ripple also decreases. Thus, to increase the power transferred between the primary and secondary windings, it is preferable to have a lower number of turns on the secondary winding. A comparison of the voltages and power present on the secondary winding of an exemplary sliding transformer as a result of different numbers of turns on the secondary winding is presented in Table 2 below. The amplitude of input

21

voltage is constant at 110 VAC and the frequency of the input voltage is constant at sixty Hertz.

TABLE 2

	Secondary Turns		
	60	40	20
	V_{avg} (V)	80	81
V_{ripple} (V_{pk-pk})	30	37	38
P_{avg} (W)	713	705	745

In addition, the present inventors have identified that the effect of increasing the frequency of the voltage supplied to the primary winding 172 has less impact on the voltage drop when the number of turns of the secondary winding 182 is decreased. For example, when the number of turns on the secondary winding is twenty turns, the average voltage remains about constant as the frequency of the voltage supplied to the primary winding increases. In fact, the average voltage increases slightly as the voltage ripple decreases providing an improved voltage on the secondary winding. A comparison of the voltages and power present on the secondary winding of another exemplary sliding transformer is presented in Table 3 below. The amplitude of input voltage is constant at 110 VAC and the number of turns on the secondary winding is constant at twenty turns.

TABLE 3

	Frequency	
	60 Hz	1000 Hz
	V_{avg} (V)	82
V_{ripple} (V_{pk-pk})	38	2
P_{avg} (W)	745	770

According to one embodiment of the invention, each of the primary and secondary windings have the same number of turns and, therefore, have a 1:1 turns ratio. The primary winding 172 includes a first coil extending along the length of each track segment 12 and each mover 100 includes a secondary winding 182 having eighty or fewer turns and, preferably, between twenty and sixty turns. The primary winding is connected to a utility supply and, therefore, receives a fixed sixty hertz input voltage. Connecting the primary winding directly to the utility supply provides a reduced system cost by not requiring a power converter to supply a variable frequency voltage to each primary winding.

In alternate embodiments, however, it is contemplated that a power converter 350 is provided to supply a variable frequency voltage to the primary winding 172. When a power converter is provided to supply voltage to the primary winding 172, the frequency of the voltage may be supplied at 200 Hz or greater and, preferably at 100 Hz or greater.

It is further contemplated that the turns ratio between the primary and secondary windings may be varied.

It is further contemplated that the mover 100 may include an energy storage device to supplement operation of the motor drive 200 or power converter 260. During, for example, periods of short term power loss, the energy

22

storage device may allow the motor drive 200 or power converter 260 to continue operation. The energy storage device may be the DC bus capacitor 214, 366 present in the motor drive 200 or power converter 260, respectively. The DC bus capacitor may be sized, for example, to include sufficient power to allow a mover 100 to traverse a gap between primary windings 172. Such a gap may exist between track segments 12 if separate primary windings 172 are provided on each segment. Optionally, the energy storage device may include a larger capacity and may be, for example, a super capacitor or a battery, where the energy storage device may provide sufficient energy, for example, such that the mover 100 may traverse one or more track segments that do not include a primary winding. Thus, the mover 100 may receive power during one segment of the track and utilize the stored power along another segment of the track.

According to another embodiment of the invention, an optical transmitter 505 wirelessly provides power from the track 10 to each mover 100 travelling along the track 10. According to the embodiment illustrated in FIG. 22, a utility power supply 171 is connected to the optical transmitter 505. The optical transmitter 505 may include the rectifier circuit 500 and drive circuit 502 to convert the AC voltage from the utility power supply 171 to a desired DC voltage to power the laser diodes 504 in the transmitter 505. One or more optical devices, such as filters and/or lenses may be mounted between the laser diode 504 and an opening 506 in the housing 503 through which the light 508 is emitted. The filters and/or lenses may remove unwanted components and orient or focus the light beams emitted from the laser diodes 504 prior to transmission. Although illustrated and discussed herein with respect to laser diodes 504, it is contemplated that various other types of lasers may be mounted to the track 10 and emit light for transferring power to the movers 100. The laser may be, but are not limited to, a gas laser, a solid-state laser, or a chemical laser.

The laser is selected such that a sufficient amount of power may be transmitted via the optical beam to each mover 100 according to the application requirements. An electronic actuator, for example, may energize intermittently and require only a few watts to tens of watts of power to activate. The light emitted 508 may only be required to transfer a corresponding level of power to the mover 100. Further, if an energy storage device 518 is provided on the mover 100, the light 508 may transmit a fraction of the required power on a continuous basis. When the actuator is not energized, the energy transmitted from the laser is stored in the energy storage device 518. When the actuator is energized, the stored energy is delivered to the actuator to supplement the energy transmitted by the laser. Thus, the level of energy transmitted by the laser must only be sufficient to charge the energy storage device 518 between the intermittent activation of the actuator. In another embodiment, the drive coils 250 may be mounted to the mover 100 and sufficient power must be supplied to the mover 100 to energize the drive coils 250 to control travel of the mover 100 along the track 10. It may be desirable to supply hundreds of watts or up to one kilowatt of power to the mover 100 to supply sufficient power to energize the drive coils 250.

An optical receiver 510 is mounted to each mover 100 to receive the light 508 beam from the transmitter 505 as the mover 100 travels along the track 10. The receiver is any device that converts light energy into electrical energy. According to the illustrated embodiment, the receiver 510 includes one or more photovoltaic modules and may form a

photovoltaic array. As illustrated in FIG. 19, the optical transmitter 505 may be offset from the receiver 510 such that the receiver 510 does not mechanically interfere with the transmitter 505 as the mover 100 passes the transmitter 505. The opening 506 in the housing 503 may be directed toward the receiver 510 such that the light 508 is emitted across the gap separating the transmitter 505 and the receiver 510. As the mover 100 travels along the track, the distance between the transmitter 505 and receiver 510 will change and, therefore, the location on the receiver at which the light 508 is incident will change. When the mover 100 is distant from the transmitter 505, the light 508 will fall on the portion of the mover 100 furthest from the track 10, and when the mover 100 is proximate the transmitter 505, the light 508 will fall on the portion of the mover 100 closest to the track 10. Thus, the optical receiver 510 may extend along the width of the bottom member 106 of the mover 100 to provide the longest distance over which the receiver will receive the light 508. The optical transmitter 505 and receiver 510 are preferably configured to allow the emitted light 508 to fall on the receiver 510 over the length of at least one track segment 12. Thus, a separate transmitter 505 may be provided on each track segment 12 to provide power to each mover 100 traveling along the track segment 12.

In the motion control system, multiple movers 100 may travel along a track segment 12. In the illustrated embodiment, a first mover 100 located in front of a second mover 100 may cause interference between the optical transmitter 505 and the receiver 510 on the second mover 100. Therefore, multiple transmitters 505 may be mounted on the track segment 12 to provide power to each mover 100 present on the segment 12. The mounting fixture 501 may extend downward for a further distance and multiple transmitters 505 may be located one below the other along the mounting fixture 501. The receivers 510 may similarly be offset below each other on successive movers 100 such that each transmitter 505 may emit light 508 to a different receiver 510. The number of transmitters and locations of receivers 510 correspond to a maximum number of movers 100 supported by a track segment 12.

As previously indicated, the mover 100 may include an energy storage device to supplement operation of the motor drive 200 or power converter 520. During, for example, periods of short term power loss, the energy storage device may allow the motor drive 200 or power converter 520 to continue operation. The energy storage device may be the DC bus capacitor 214, 532 present in the motor drive 200 or power converter 520, respectively. The DC bus capacitor may be sized, for example, to include sufficient power to allow a mover 100 to traverse a gap between track segments 12 during which no light 508 is incident on the optical receiver 510. Optionally, the energy storage device may include a larger capacity and may be, for example, a super capacitor or a battery, where the energy storage device may provide sufficient energy, for example, such that the mover 100 may traverse one or more track segments that do not include an optical transmitter 505. Thus, the mover 100 may receive power along one segment of the track and utilize the stored power along another segment of the track.

According to another embodiment of the invention, a generator 402 provides power the mover 100 while traveling along the track 10. According to the embodiment illustrated in FIGS. 15-18, a drive wheel 406 is mounted to the mover 100 such that it engages a portion of the track 10 as the mover 100 travels along the track 10. A drive shaft 404 extends between the drive wheel 406 and the generator 402. The drive shaft 404 causes a rotor within the generator to

turn. Permanent magnets mounted to the rotor generate a magnetic field which, in turn, induces a current and voltage in the stator of the generator 402, thereby generating electric power due to rotation of the drive wheel 406. As discussed above, the electric power is provided to a power converter 410 for use by electrical devices 300 or by a motor drive 200 mounted on the mover 100.

Each generator 402 is configured to generate electrical power as the mover 100 travels. The amount of power is determined by the construction of the generator 402, the speed of travel of the mover 100 and by the amount of travel performed by the mover 100. The generator 402 may be selected such that a sufficient amount of power is generated on mover 100 to power one or more electronic devices 300 mounted to the mover 100. An electronic actuator, for example, may energize intermittently and require only a few watts to tens of watts of power to activate. The generator 402 may only be required to output a corresponding level of power to the mover 100. If the mover 100 is travelling during actuation, the generator 402 may supply power directly to the electronic device 300. If actuation is required when the mover 100 is stopped, an energy storage device 418 may be provided on the mover 100. The energy storage device 418 receives power output from the generator 402 while the mover 100 is moving. When the actuator is energized, the stored energy is delivered to the actuator. Thus, the level of energy output from the generator 402 must only be sufficient to charge the energy storage device 418 between the intermittent activation of the actuator. In another embodiment, the drive coils 250 may be mounted to the mover 100 and sufficient power must be supplied to the mover 100 to energize the drive coils 250 to control travel of the mover 100 along the track 10. It may be desirable to supply hundreds of watts or up to one kilowatt of power to the mover 100 to supply sufficient power to energize the drive coils 250. Initially sufficient energy must be stored in the energy storage device 418 to get the mover 100 started. Once the mover 100 is travelling, the power output from the generator is provided to the motor drive 200 for subsequent energization of the drive coils 250.

It is contemplated that the generator 402 may be used in combination with either the sliding transformer or the optical transmitter 505 to supply power to the mover 100. A portion of the electrical power required by the mover 100 may be output from the generator 402 and a portion of the electrical power may be transmitted to the mover via either the sliding transformer or the optical transmitter. Further, while separate power converters are illustrated, it is contemplated that portions of the power converters may be combined to reduce the number of components present on the mover 100. For example, a common dc bus may be used with a generator, sliding transformer, motor drive, and an electronic device present on the mover 100. The AC power supplied from either the generator or the sliding transformer may be provided via respective rectifier sections to the dc bus and the motor drive and the electronic device may receive power from the dc bus via respective inverter sections.

It should be understood that the invention is not limited in its application to the details of construction and arrangements of the components set forth herein. The invention is capable of other embodiments and of being practiced or carried out in various ways. Variations and modifications of the foregoing are within the scope of the present invention. It also being understood that the invention disclosed and defined herein extends to all alternative combinations of two or more of the individual features mentioned or evident from

25

the text and/or drawings. All of these different combinations constitute various alternative aspects of the present invention. The embodiments described herein explain the best modes known for practicing the invention and will enable others skilled in the art to utilize the invention.

We claim:

1. An apparatus for providing power to a mover in a motion control system, the apparatus comprising:

a plurality of movers;
a plurality of electrical devices, wherein at least one of the electrical devices is mounted to each of the plurality of movers;

a track defining a continuous path along which each of the plurality of movers travels;

a primary winding mounted along the track, wherein the primary winding is configured to receive power from a power supply;

a plurality of secondary windings, wherein:
each secondary winding is mounted to one of the plurality of movers,

each secondary winding is generally aligned with the primary winding as the mover travels along the track,

an air gap separates each secondary winding from the primary winding, and

power from the power supply is wirelessly transferred from the primary winding to the secondary winding across the air gap; and

a plurality of power converters, wherein each of the plurality of power converters is mounted to one of the plurality of movers and is operative to receive power from the secondary winding mounted to the mover and to supply power to the at least one electrical device mounted on the mover.

2. The apparatus of claim 1 wherein:

the primary winding includes a primary forward conduction path and a primary reverse conduction path,

the primary forward conduction path and the primary reverse conduction path are spaced apart from each other and extend longitudinally in a direction of travel along the continuous path,

each secondary winding includes a secondary forward conduction path and a secondary reverse conduction path,

the secondary forward conduction path and the secondary conduction path are spaced apart from each other and extend along the mover in the direction of travel, and each of the secondary forward and reverse conduction paths are generally aligned with the primary forward and reverse conduction paths.

3. The apparatus of claim 1 further comprising a generator mounted on each of the plurality of movers, wherein the generator includes:

a drive wheel configured to engage the track and to rotate as the mover travels along the track,

a drive shaft operatively coupled to the drive wheel wherein rotation of the drive wheel causes rotation of the drive shaft, and

a rotor operatively coupled to the drive shaft to generate power on a stator when the drive shaft rotates, and wherein each of the plurality of power converters is operative to receive power from both the generator and the secondary winding.

4. The apparatus of claim 3 further comprising an electrical energy storage device, wherein:

the power converter supplies power to charge the electrical energy storage device when a magnitude of power

26

received from the generator and the secondary winding exceeds a magnitude of power demanded by the at least one electrical device mounted on the mover, and

the power converter draws power from the electrical energy storage device when the magnitude of power received from the generator and the secondary winding is less than the magnitude of power demanded by the at least one electrical device mounted on the mover.

5. The apparatus of claim 1 wherein the track includes a plurality of track segments, the primary winding includes a plurality of windings, and each of the plurality of windings for the primary winding extends longitudinally along one of the plurality of track segments.

6. The apparatus of claim 1 further comprising:

a plurality of motor drives, wherein each motor drive is mounted to one of the plurality of movers and wherein each motor drive includes:

a rectifier section, wherein an input of the rectifier section is connected to and receives power from the secondary winding mounted to the corresponding mover and an output of the rectifier section is connected to a dc bus, and

an inverter section, wherein an input of the inverter section is connected to and receives power from the dc bus and wherein the motor drive is operative to provide a variable amplitude and variable frequency voltage at an output of the inverter section; and

a plurality of drive coils mounted to each mover and connected to the output of the inverter section to receive the variable amplitude and variable frequency voltage.

7. The apparatus of claim 1 further comprising an impedance matching circuit operatively connected to the primary winding, wherein the impedance matching circuit has a resonant frequency operative to amplify a magnitude of one of a voltage and a current present on the primary winding.

8. An apparatus for providing power to a mover in a motion control system, the apparatus comprising:

a plurality of movers;

a plurality of electrical devices, wherein at least one of the electrical devices is mounted to each of the plurality of movers;

a track defining a path along which each of the plurality of movers travels;

a primary winding mounted along the track, wherein the primary winding is configured to receive power from a power supply;

a plurality of secondary windings, wherein:

each secondary winding is mounted to one of the plurality of movers,

each secondary winding includes a corresponding impedance matching circuit mounted to the corresponding mover, wherein the impedance matching circuit has a resonant frequency corresponding to a frequency present in an electromagnetic field generated by the primary winding;

each secondary winding is generally aligned with the primary winding as the mover travels along the track, and

an air gap separates each secondary winding from the primary winding; and

a plurality of power converters, wherein each of the plurality of power converters is mounted to one of the plurality of movers and is operative to receive power from the secondary winding mounted to the mover and to supply power to the at least one electrical device mounted on the mover.

9. The apparatus of claim 8 wherein:
 the primary winding mounted includes a primary forward conduction path and a primary reverse conduction path, the primary forward conduction path and the primary reverse conduction path are spaced apart from each other and extend longitudinally in a direction of travel along the continuous path,
 each secondary winding includes a secondary forward conduction path and a secondary reverse conduction path,
 the secondary forward conduction path and the secondary conduction path are spaced apart from each other and extend along the mover in the direction of travel, and each of the secondary forward and reverse conduction paths are generally aligned with the primary forward and reverse conduction paths.

10. The apparatus of claim 8 further comprising a generator mounted on each of the plurality of movers, wherein the generator includes:

- a drive wheel configured to engage the track and to rotate as the mover travels along the track,
- a drive shaft operatively coupled to the drive wheel wherein rotation of the drive wheel causes rotation of the drive shaft, and
- a rotor operatively coupled to the drive shaft to generate power on a stator when the drive shaft rotates, and wherein each of the plurality of power converters is operative to receive power from both the generator and the secondary winding.

11. The apparatus of claim 8 further comprising an electrical energy storage device, wherein:

- the power converter supplies power to charge the electrical energy storage device when a magnitude of power received from the generator and the secondary winding exceeds a magnitude of power demanded by the at least one electrical device mounted on the mover, and
- the power converter draws power from the electrical energy storage device when the magnitude of power received from the generator and the secondary winding is less than the magnitude of power demanded by the at least one electrical device mounted on the mover.

12. The apparatus of claim 8 wherein the track includes a plurality of track segments, the primary winding includes a plurality of windings, and each of the plurality of windings for the primary winding extends longitudinally along one of the plurality of track segments.

13. The apparatus of claim 8 further comprising:

- a plurality of motor drives, wherein each motor drive is mounted to one of the plurality of movers and wherein each motor drive includes:
 - a rectifier section, wherein an input of the rectifier section is connected to and receives power from the secondary winding mounted to the corresponding mover and an output of the rectifier section is connected to a dc bus, and
 - an inverter section, wherein an input of the inverter section is connected to and receives power from the dc bus and wherein the motor drive is operative to provide a variable amplitude and variable frequency voltage at an output of the inverter section; and
- a plurality of drive coils mounted to each mover and connected to the output of the inverter section to receive the variable amplitude and variable frequency voltage.

14. The apparatus of claim 8 further comprising an impedance matching circuit operatively connected to the primary winding, wherein the impedance matching circuit has a resonant frequency operative to amplify a magnitude of one of a voltage and a current present on the primary winding.

15. An apparatus for providing power to a mover in a motion control system, the apparatus comprising:

- a track;
- a primary winding mounted along the track, wherein the primary winding is operative to receive power from a power supply and to establish an electromagnetic field around the primary winding when the power from the power supply is present; and
- a plurality of movers operative to travel along the track, wherein each mover includes:
 - a secondary winding mounted to the mover such that it is generally aligned with and spaced apart from the primary winding as the mover travels along the track, wherein a current is induced in the secondary winding for wireless power transfer from the primary winding to the secondary winding as a result of the electromagnetic field around the primary winding as the mover travels along the track; and
 - at least one electrical device mounted to the mover, wherein the electrical device is configured to receive power for operation from the power wirelessly transferred to the winding.

16. The apparatus of claim 15 further comprising an impedance matching circuit operatively connected to the primary winding, wherein the impedance matching circuit has a resonant frequency operative to amplify a magnitude of one of a voltage and a current present on the primary winding.

17. The apparatus of claim 15 further comprising an impedance matching circuit operatively connected to the secondary winding on each of the plurality of movers, wherein the impedance matching circuit has a resonant frequency corresponding to a frequency present in the electromagnetic field generated by the primary winding.

18. The apparatus of claim 15 wherein each mover further includes a power converter operative to receive power from the secondary winding and to supply power to the at least one electrical device mounted on the mover.

19. The apparatus of claim 15 wherein the at least one electrical device mounted to the mover is a motor drive, wherein each motor drive includes:

- a rectifier section, wherein an input of the rectifier section is connected to and receives power from the secondary winding mounted to the corresponding mover and an output of the rectifier section is connected to a dc bus, and
- an inverter section, wherein an input of the inverter section is connected to and receives power from the dc bus and wherein the motor drive is operative to provide a variable amplitude and variable frequency voltage at an output of the inverter section; and wherein each mover further includes a plurality of drive coils mounted to each mover and connected to the output of the inverter section to receive the variable amplitude and variable frequency voltage.