



US010801179B2

(12) **United States Patent**
Moen et al.

(10) **Patent No.:** **US 10,801,179 B2**
(45) **Date of Patent:** **Oct. 13, 2020**

(54) **HYDRAULIC FLUID STORAGE TANK INCLUDING QUICK CONNECT COUPLING**

USPC 220/563, 562, 564, 86.1, 601, 661, 220/203.29, 203.27, 203.19, 554, 553; 222/568, 567, 566; 138/39, 40, 37
See application file for complete search history.

(71) Applicant: **CNH Industrial America LLC**, New Holland, PA (US)

(72) Inventors: **Richard A. Moen**, Glenwood, MN (US); **William A. Roach**, Lake Lillian, MN (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **CNH Industrial America LLC**, New Holland, PA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 87 days.

- 761,548 A * 5/1904 Sheaff B65D 83/38 222/394
- 1,616,008 A * 2/1927 Stout B64D 37/02 220/563
- 2,600,876 A 6/1952 Jauch et al.
- 2,628,741 A * 2/1953 Wilds B63B 11/04 220/86.1
- 3,298,560 A * 1/1967 Anderson B29D 22/00 220/567.1

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **15/843,711**

(22) Filed: **Dec. 15, 2017**

(65) **Prior Publication Data**

US 2019/0186103 A1 Jun. 20, 2019

CN 203516235 4/2014
DE 102011112576 A1 * 3/2013 F16K 15/147

Primary Examiner — Robert J Hicks

(74) *Attorney, Agent, or Firm* — Rebecca L. Henkel; Rickard K. DeMille

(51) **Int. Cl.**
E02F 9/08 (2006.01)
E02F 9/22 (2006.01)
B60K 15/067 (2006.01)
A01B 63/10 (2006.01)
A01M 7/00 (2006.01)


(57) **ABSTRACT**

A storage system for storing hydraulic fluid used to drive hydraulically driven components of an agricultural implement and of filling the same are provided. The storage system includes a tank having an underside. The tank has a cavity in an interior thereof for receiving the hydraulic fluid therein. A quick connect coupling is operatively connected to the underside of the tank and has an output end in communication with the cavity in the tank and an input end connectable to a hydraulic fluid source. The quick connect coupling is configured to allow for flow from the input end to the output end thereof.

(52) **U.S. Cl.**
CPC **E02F 9/0883** (2013.01); **E02F 9/2264** (2013.01); **A01B 63/1006** (2013.01); **A01M 7/0082** (2013.01); **B60K 15/067** (2013.01)

(58) **Field of Classification Search**
CPC E02F 9/0883; E02F 9/2264; E02F 9/2271; E02F 9/22; A01B 63/1006; B60K 15/067; B60K 15/063; B60K 15/03006; B60K 15/03; B60K 15/04; B65D 11/08; B65D 25/48; B65D 83/28; B65D 51/1644; B65D 51/1661; B65D 51/16; F16K 24/04; F16K 24/02

13 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,692,051	A *	9/1972	Eyb	B60K 15/03 137/544
4,006,761	A	2/1977	Bonafous	
4,268,156	A	5/1981	Kostiner	
4,488,701	A	12/1984	Leigh-Monstevens	
4,881,581	A	11/1989	Hollerback	
5,083,433	A	1/1992	Leigh-Monstevens	
5,141,013	A	8/1992	Zink et al.	
5,641,003	A	6/1997	Rey et al.	
5,740,846	A	4/1998	Larson et al.	
6,302,167	B1	10/2001	Hollub	
6,732,774	B1	5/2004	Seckel	
7,565,986	B2 *	7/2009	Brandner	B29C 49/22 220/562
2003/0010196	A1 *	1/2003	Smith	B62D 49/02 91/536
2008/0236847	A1	10/2008	Sanchez et al.	
2010/0072200	A1 *	3/2010	Marquardt	B60K 15/04 220/86.2
2015/0022334	A1	1/2015	Guillory et al.	
2015/0059709	A1 *	3/2015	Oohashi	B60K 15/03 123/509
2015/0276114	A1 *	10/2015	Bishop, Jr.	F16L 55/00 285/45
2016/0176278	A1	6/2016	Bletscher et al.	

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7



1

HYDRAULIC FLUID STORAGE TANK INCLUDING QUICK CONNECT COUPLING

FIELD OF THE INVENTION

This invention relates generally to hydraulic drive systems for agricultural implements, and in particular, to a hydraulic fluid storage tank for a hydraulic drive system of an agricultural implement that includes a quick connect coupling for facilitating the filling of the hydraulic fluid storage tank by a user.

BACKGROUND AND SUMMARY OF THE INVENTION

Agricultural implements, such as agricultural chemical sprayers, often include one or more extendable booms configured to spray liquid treatment materials onto established crops. Typically, agricultural chemical sprayers are towed by a tractor or other vehicle, or are constructed as a dedicated, self-propelled sprayer vehicle. Such sprayers, whether towed or self-powered, commonly include a tank or reservoir supported by a frame of the underlying vehicle and a pump system configured to communicate the liquid treatment materials to the respective booms for spraying.

As is conventional, an agricultural chemical sprayer requires a hydraulic power system configured to provide pressurized hydraulic fluid flow to drive the various hydraulically driven components of the sprayer (e.g., the driving and steering system, the cylinders controlling the one or more extendable booms, etc.) associated with the operation thereof. The hydraulic drive system includes a hydraulic reservoir or fluid storage tank to provide fluid storage for the system. The hydraulic fluid storage tank is operatively connected to various conduits which are configured to convey the hydraulic fluid between various hydraulic-driven components and the hydraulic fluid storage tank.

It can be appreciated that the level of hydraulic fluid in the storage tank must be maintained for proper performance of the various hydraulic driven components of the sprayer and to prevent the premature malfunction thereof.

As noted above, it is intended for an agricultural chemical sprayer to spray liquid treatment materials onto established crops. Hence, the frame of the agricultural chemical sprayers must provide adequate ground clearance to prevent damage to the crops during the application of the liquid treatment materials. As such, the hydraulic fluid storage tank of the agricultural chemical sprayers is often mounted at the top of the frame. Further, the fill spout of the hydraulic fluid storage tank is often provided at the top of the tank. Consequently, given the position of the hydraulic fluid storage tank on the frame and the height of this fill spout, it is not possible for an operator to fill the hydraulic fluid storage tank with fluid while standing on the ground, thereby necessitating the use of a ladder by the operator. This process increases the time associated with maintenance of the agricultural chemical sprayer which, in turn, increases the costs and decreases the efficiency associated with operation of the agricultural chemical sprayer.

Therefore, it is a primary object and feature of the present invention to provide a hydraulic fluid storage tank for a hydraulic drive system of an agricultural implement that simplifies the process associated with filling the storage tank with hydraulic fluid.

It is a further object and feature of the present invention to provide a hydraulic fluid storage tank for a hydraulic drive

2

system of an agricultural implement that includes a quick connect coupling for facilitating the filling of the hydraulic fluid storage tank by a user.

It is a still further object and feature of the present invention to provide a hydraulic fluid storage tank for a hydraulic drive system of an agricultural implement that is simple to fill and inexpensive to manufacture.

In accordance with the present invention, a storage tank is provided for storing hydraulic fluid used to power hydraulically driven components of an agricultural implement. The storage tank includes an upper wall, a lower wall and a plurality of side walls interconnecting the upper and lower walls. The upper, lower and side walls define a cavity for receiving the hydraulic fluid therein. A quick connect coupling has an output end communicating with the second end of the passageway of the spout and an input end connectable to a hydraulic fluid source. The quick connect coupling is configured to allow for flow from the input end to the output end thereof.

A baffle is disposed within the cavity and divides the cavity into first and second portions. The baffle is configured to reduce flow of hydraulic fluid between first and second portions during transport of the agricultural implement. The storage tank further includes a tubular, hydraulic fluid receiving spout extending through the upper wall. The spout defines a passageway having a first end communicating with the cavity and a second end communicating with an environment outside of the storage tank. An end cap is receivable on the second spout for selectively closing off the first end of the passageway of the spout.

A suction screen defines a passageway having a first end communicating with cavity and a second end communicating with an environment outside of the storage tank. The suction screen is one of a plurality of defining a generally tubular outlet tubes. Each of the plurality of suction screens defines a passageway having a first end communicating with cavity and a second end communicating with an environment outside of the storage tank. A cleanout cover is positioned in an aperture through one of the side walls of the plurality of side walls. The cleanout cover may be a first cleanout cover and a second cleanout cover may be positioned in a second aperture through the one of the side walls of the plurality of side walls.

In accordance with a further aspect of the present invention, a storage system is provided for storing hydraulic fluid used to drive hydraulically driven components of an agricultural implement. The storage system includes a tank having an underside. The tank has a cavity in an interior thereof for receiving the hydraulic fluid therein. A quick connect coupling is operatively connected to the underside of the tank and has an output end in communication with the cavity in the tank and an input end connectable to a hydraulic fluid source. The quick connect coupling is configured to allow for the flow from the input end to the output end thereof.

The tank includes an upper wall, a lower wall and a plurality of side walls interconnecting the upper and lower walls. The lower wall at least partially defines the underside of the tank. A tubular, hydraulic fluid receiving spout defines a passageway therethrough. The passageway has a first end communicating with the cavity in the tank and a second end communicating with the output end of the quick connect coupling. A baffle is disposed within the cavity and divides the cavity into first and second portions. The baffle is configured to reduce flow of hydraulic fluid between first and second portions during transport of the agricultural implement.

3

A tubular, hydraulic fluid receiving spout extends through the tank. The spout defines a passageway having a first end communicating with the cavity and a second end communicating with an environment outside of the storage tank. The storage system includes at least one suction screen. The at least one suction screen defines a passageway having a first end communicating with cavity and a second end communicating with an environment outside of the tank. At least one cleanout cover is positioned within a corresponding aperture in the tank.

In accordance with a still further aspect of the present invention, a method of filling a storage tank with hydraulic fluid used to drive hydraulically driven components of an agricultural implement is provided. The method includes the steps of operatively connecting a quick connect coupling to an underside of the storage tank. The quick connect coupling has a output end in communication with an interior of the storage tank and an input end. The input end of the quick connect coupling is connected to a hydraulic fluid source and hydraulic fluid is pumped from the hydraulic fluid source to the input end of the quick connect coupling under pressure. The quick connect coupling is configured to allow for the hydraulic fluid received at the input end of the quick connect coupling to flow from the input end to the output end.

The tank includes an upper wall, a lower wall and a plurality of side walls interconnecting the upper and lower walls. The lower wall at least partially defines the underside of the tank. A baffle is disposed within the interior of the storage tank so as to divide the interior of the storage tank into first and second portions. The baffle is configured to reduce flow of hydraulic fluid between first and second portions during transport of the agricultural implement. A tubular, hydraulic fluid receiving spout extends through the storage tank. The spout defines a passageway having a first end communicating with the interior of the storage tank and a second end communicating with an environment outside of the storage tank. The interior of the storage tank is operatively connected to the input of a pump.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings furnished herewith illustrate a preferred construction of the present invention in which the above advantages and features are clearly disclosed as well as others which will be readily understood from the following description of the illustrated embodiment.

In the drawings:

FIG. 1 is side elevational view of a tractor incorporating a hydraulic fluid storage tank in accordance with present invention;

FIG. 2 is a schematic view of a hydraulic drive system incorporating the hydraulic fluid storage tank of the present invention;

FIG. 3 is an isometric view of the hydraulic fluid storage tank of the present invention;

FIG. 4 is a side elevational view of the hydraulic fluid storage tank of the present invention;

FIG. 5 is a cross-sectional view of the hydraulic fluid storage tank of the present invention taken along line 5-5 of FIG. 4;

FIG. 6 is a cross-sectional view of the hydraulic fluid storage tank of the present invention taken along line 6-6 of FIG. 4;

FIG. 7 is a cross-sectional view of the hydraulic fluid storage tank of the present invention taken along line 7-7 of FIG. 4;

4

FIG. 8 is a front elevational view of the hydraulic fluid storage tank of the present invention; and

FIG. 9 is a cross-sectional view of the hydraulic fluid storage tank of the present invention taken along line 9-9 of FIG. 4.

DETAILED DESCRIPTION OF THE DRAWINGS

Referring now to the drawings and specifically to FIG. 1, an exemplary self-propelled, agricultural chemical sprayer is generally designated by the reference numeral 10. It is intended for sprayer 10 to be a high-clearance crop vehicle, wherein the term "high-clearance" means a vehicle that is configured to traverse established crops, particularly more vertically oriented crops such as corn, etc., with negligible interaction between the established crop and the chassis, frame members such as axles, and wheels of the underlying vehicle. Such vehicles provide a vertical cross-sectional shape wherein the vehicle can traverse established vegetation, such as corn or other premature crop materials, as well as, vegetables or other mature and premature lower growing crops, without interfering with or destroying the desired structures of the plant or crop.

Although some crop materials can tolerate limited interaction with a passing vehicle, the high-clearance vehicle is constructed to allow passage of the vehicle over most established vegetation without adversely impacting the health or productivity of the vegetation. It is appreciated that many agricultural vehicles that are not provided in a high-clearance configuration provide adequate clearance for immature and lower growing vegetation but that many such vehicles increase the potential of driving down established crops. Further, for established and more vertically oriented crop materials, such as corn or the like, use of more conventional clearance vehicles post only early crop growth stages, would interfere with the desired treatment of the established crop materials and risk unnecessary damage to the underlying crop materials.

Sprayer 10 includes a chassis or frame 12 having one or more tires or wheels 14 associated therewith. Each of wheels 14 rotate about a respective generally horizontal axis and one or more of wheels 14 is turnable about a generally vertical axis to effectuate turning or changing the direction of travel of sprayer 10. It is appreciated that changes to the direction of travel of sprayer 10 can be effectuated in a number of manners including manually and/or automatically if sprayer 10 is equipped with such remote control or automatic operation methodologies.

As is conventional, sprayer 10 includes an operator area or cab 16 supported on frame 12 and a power plant or engine (not shown) supported on frame 12 forwardly of cab 16. Sprayer 10 may include one or more extendable booms (not shown) configured to spray liquid treatment materials on desired crops in an agricultural field, a tank or reservoir for housing liquid treatment materials to be sprayed, and a pump system configured to communicate the liquid treatment materials to the respective booms for spraying.

Referring to FIG. 2, the agricultural chemical sprayer 10 further includes hydraulic drive system 22 configured to provide pressurized hydraulic fluid flow via pumps 25 to drive the various hydraulically driven components 24 of the sprayer (e.g., the steering system, the cylinders controlling the one or more extendable booms, etc.) associated with the operation thereof. Hydraulic drive system 22 includes hydraulic fluid storage tank 26 fluidically coupled to the one of more pumps 25 in any conventional manner, such as by one or more conduits, collectively depicted as line 28. The

5

one or more pumps **25** are, in turn, fluidically coupled to the hydraulically driven components **24** in any conventional manner, such as by one or more conduits, collectively depicted as line **29**. As best seen in FIG. 1, storage tank **26** is operatively connected to frame **12** at a location adjacent cab **16** in any conventional manner such as by welding, bolts or the like.

Referring to FIG. 3-9 storage tank **26** includes a generally flat, upper wall **34** and generally flat lower wall **36** interconnected by side walls **38**, **40**, **42** and **44**. Inner surfaces **38a**, **40a**, **42a** and **44a** of side walls **38**, **40**, **42** and **44**, respectively, define cavity **46** within the interior of storage tank **26**, as hereinafter described. Outer surface **48** of upper wall **34** includes first and second generally U-shaped lifting hooks **50** and **52**, respectively, projecting therefrom. Terminal ends **50a** and **50b** of lifting hook **50** and terminal ends **52a** and **52b** of lifting hook **52** are interconnected to outer surface **48** of upper wall **34** by means of welding of the like. It is intended for lifting hooks **50** and **52** to facilitate the positioning and mounting of storage tank **26** to frame **12**, as heretofore described. Weld stud **54** projects axially from outer surface **48** of upper wall **34** to allow for a wire harness (not shown) to be secured thereto.

Upper wall **34** further includes first and second apertures **56** and **58**, respectively, therein. First aperture **56** in upper wall **34** is adapted for receiving hydraulic fluid receiving spout **60** therethrough. Spout **60** is generally tubular in structure and includes an inner surface **62** defining passageway **64**. Spout **60** has a first end **66** received within cavity **46** within the interior of storage tank **26** such that a first end **68** of passageway **64** communicates with cavity **46** and a second end **70** external of storage tank **26**. Outer surface **72** of spout **60** is fixed to upper wall **34** about first aperture **56** such as by welding or the like. It is contemplated to fix spout **60** to upper wall **34** such that passageway **64** through spout **60** extends along an axis at an acute angle to outer surface **48** of upper wall **34**. End cap **74** is removeably positionable about second end **70** of spout **60** in a conventional manner to prevent unintended materials from entering cavity **46** in storage tank **26** through passageway **64** of spout **60**. In addition, end cap **74** also acts as a breather to limit air pressure fluctuations in storage tank **26** due to effects that change the volume of hydraulic fluid therein (e.g., thermal expansion/contraction, cylinder extension/retraction, etc.).

Second aperture **58** in upper wall **34** is adapted for temperature and fluid level sender **76** therethrough. Sender **76** is generally tubular in structure and includes an inner surface **78** defining passageway **80**. Sender **76** has a first end **82** received within cavity **46** within the interior of storage tank **26** such that a first end **84** of passageway **80** communicates with cavity **46** and a second end **86** external of storage tank **26**. Temperature sender **87** and fluid level sender **88** are positioned within passageway **80** adjacent first end **84** thereof and operatively connected to corresponding indicator unit[s] (not shown) within cab **16** of sprayer **10** by line **90** passing through second end **86** of sender **76**. As is conventional, the indicator unit[s] (not shown) within cab **16** of sprayer **10** measure and display the temperature and the fluid level in cavity **46** in storage tank **26**. Outer surface **92** of sender **76** is fixed to upper wall **34** about second aperture **58** such as by welding or the like. It is contemplated to fix sender **76** to upper wall **34** such that passageway **80** through sender **76** extends along an axis at an acute angle to outer surface **48** of upper wall **34**.

Upper wall **34** is defined by generally parallel, first and second side edges **94** and **96**, respectively, interconnected by generally parallel, first and second end edges **98** and **100**,

6

respectively. Similarly, lower wall **36** is defined by generally parallel, first and second side edges **102** and **104**, respectively, interconnected by generally parallel, first and second end edges **106** and **108**, respectively. First side edge **94** of upper wall **34** is interconnected to first side edge **102** of lower wall **36** by side wall **38**. Side wall **38** includes first and second sides **110** and (not shown), respectively.

Side wall **42** extends between second side edge **96** of upper wall **34** and second side edge **104** of lower wall **36**. Side wall **42** includes an upper portion **114** extending from second side edge **96** of upper wall **34** and diverging from side wall **38**. Upper portion **114** includes first and second side edges **117** and **119**, respectively, and terminates at a lower edge **116** generally parallel to second side edge **96** of upper wall **34**. Aperture **120** extends through upper portion **114** and is adapted for receiving a cleanout cover **122** therein for allowing access to the inside of storage tank **26** for cleaning either during manufacture or field service. Intermediate portion **118** of side wall **42** extends from lower edge **116** of upper portion **114** and includes first and second side edges **121** and **123**, respectively. Intermediate portion **118** of side wall **42** lies in a plane generally parallel to upper and lower walls **34** and **36**, respectively, and terminates at terminal edge **124**. U-shaped lifting hook **126** projects from outer surface **128** of intermediate portion **118** of side wall **42**.

Lower portion **130** of side wall **42** extends from terminal edge **124** of intermediate portion **118** and includes first and second side edges **132** and **134**, respectively. Lower portion **130** of side wall **42** includes a first aperture **136** extending through lower portion **130** and is adapted for receiving a cleanout cover **138** therein for allowing access to the inside of storage tank **26** for cleaning either during manufacture or field service. In addition, lower portion **130** of side wall **42** further includes first and second ports **141** and **143**, respectively, projecting therefrom. First and second ports **141** and **143**, respectively, are intended to allow fluid conveyance to and from the tank.

First side edges **117**, **121**, and **132** of upper, intermediate and lower portions **114**, **118**, and **130**, respectively, collectively define first side edge **140** of side wall **42**. Similarly, second side edges **119**, **123**, and **134** of upper, intermediate and lower portions **114**, **118**, and **130**, respectively, collectively define second side edge **142** of side wall **42**. Side wall **40** extends between first end edge **98** of upper wall **34** and first end edge **106** of lower wall **36** so as to interconnect upper and lower walls **34** and **36**, respectively, as heretofore described. In addition, side wall **40** extends between first side edge **140** of side wall **42** and first side **110** of side wall **38** so as to interconnect side walls **38** and **42**. As best seen in FIG. 8, side wall **40** includes an upper portion **150** which is generally perpendicular to upper wall **34** and terminates at terminal end **152** which is generally parallel to first end edge **98** of upper wall **34**. Lower portion **154** of side wall **40** extends from terminal end **152** of upper portion **150** of side wall **40** at an acute angle to upper wall **34**. Sight level gauge **153** may be provided on side wall **40** to allow a user to visually monitor the hydraulic fluid in cavity **46** with storage tank **26** and mounting bracket **155** may project from side wall **40** to facilitate the mounting of storage tank **26** to frame **12**.

Side wall **44** extends between second end edge **100** of upper wall **34** and second end edge **108** of lower wall **36** so as to interconnect upper and lower walls **34** and **36**, respectively, as heretofore described. In addition, side wall **44** extends between second side edge **142** of side wall **42** and second side (not shown) of side wall **38** so as to interconnect

side walls **38** and **42**. Side wall **44** includes an upper portion **156** at an obtuse angle to upper wall **34** and terminates at terminal end **158** which is generally parallel to and is vertically spaced from intermediate portion **118** of side wall **42**.

Lower portion **160** of side wall **44** extends from terminal end **158** of upper portion **156** of side wall **44** and is generally perpendicular to upper wall **34**. Lower portion **160** of side wall **44** further includes first and second ports **159** and **161**, respectively, projecting therefrom. First and second mounting ports **159** and **161**, respectively, are intended to allow fluid conveyance to and from the tank. A plurality of weld studs **163** project axially from side wall **44** to allow for a wire harness (not shown) to be secured thereto. In addition, it is contemplated to provide first and second apertures **164** and **166**, respectively, through lower portion **160** of side wall **44** to accommodate first and second suction screens **168** and **170**, respectively, therethrough. Mounting bracket **157** may project from lower portion **160** of side wall **44** to facilitate the mounting of storage tank **26** to frame **12**.

Suction screen **168** is generally tubular in structure and includes an inner surface **169** defining passageway **172**. Suction screen **168** has a first end **174** received within cavity **46** within the interior of storage tank **26** such that a first end **175** of passageway **174** communicates with cavity **46** and a second end **176** is external of storage tank **26**. Outer surface **178** of suction screen **168** is threaded into first aperture **164** through to side wall **44**. It is contemplated to fix suction screen **168** to side wall **44** such that passageway **174** through suction screen **168** extends along an axis generally parallel upper wall **34**. Suction screen **168** is operatively connectable to a corresponding pump **25** providing pressurized hydraulic fluid flow to drive various hydraulically driven components of the sprayer (e.g., the steering system, the cylinders controlling the one or more extendable booms, etc.) associated with the operation thereof.

Suction screen **170** is generally tubular in structure and includes an inner surface **180** defining passageway **182**. Suction screen **170** has a first end **184** received within cavity **46** within the interior of storage tank **26** such that a first end **185** of passageway **184** communicates with cavity **46** and a second end **186** is external of storage tank **26**. Outer surface **188** of suction screen **170** is threaded into second aperture **166** through side wall **44**. It is contemplated to fix suction screen **170** to side wall **44** such that passageway **184** through outlet tube **170** extends along an axis generally parallel upper wall **34**. Suction screen **170** is operatively connected to a corresponding pump **25** for providing pressurized hydraulic fluid flow to drive various hydraulically driven components of the sprayer (e.g., the steering system, the cylinders controlling the one or more extendable booms, etc.) associated with the operation thereof.

Lower wall **36** includes an aperture **190** therethrough to accommodate hydraulic fluid receiving spout **192**. More specifically, spout **192** is generally tubular in structure and includes an inner surface **194** defining passageway **195**. Spout **192** has an inner end **196** received within cavity **46** within the interior of storage tank **26** and an outer end **197** such that a first end **198** of passageway **195** communicates with cavity **46** and a second end **200**. Outer surface **202** of spout **192** is fixed to lower wall **36** about aperture **190** such as by welding or the like. It is contemplated to fix spout **192** to lower wall **36** such that passageway **195** through spout **192** extends along an axis generally perpendicular to lower wall **36**. It is intended for spout **192** to prevent hydraulic fluid from draining out of storage tank **26** in the event of a leak in a quick connect coupling **204**, hereinafter described.

Inner end **196** of spout **192** is provided at generally the same vertical level as the fluid level sender **88**.

Quick connect coupling **204** is operatively connected to outer end **197** of spout **192**. Coupling **204** includes a connector housing **206** having an input end **208** adapted for connecting to a terminal output end of a fill hose **207**, FIG. 2, in a mating relationship and an output end **210** coupled to outer end **197** of spout **192**. A valve, generally designated by the reference numeral **212**, is provided within connector housing **206** between input and output ends **208** and **210**, respectively. Valve **212** includes an internal seal **214** movable between a first position wherein seal **214** blocks the flow of fluid therepast and a second position wherein **214** allows fluid to flow through quick connect coupling **204** from input end **208** to output end **210**. Valve **212** is biased toward the first position to prevent hydraulic fluid from exiting cavity **46** within the interior of storage tank **26** therepast. It is contemplated for valve **212** to be moved between the first position to the second position in any conventional manner, such as by the connection of the terminal output end of the fill hose **207** to input end **208** of connector housing **206** of coupling **204** or by fluidic pressure, as hereinafter described.

Partition **220** is positioned in cavity **46** within the interior of storage tank **26** between inner surfaces **38a**, **40a**, **42a** and **44a** of side walls **38**, **40**, **42** and **44**, respectively, so as to divide cavity **46** into an upper portion **221** and a lower portion **223**. More specifically, partition **220** includes a first, horizontal portion **222** lying in a plane generally parallel to upper wall **34** and extending between inner surfaces **38a**, **42a** and **44a** of side walls **38**, **42** and **44**, respectively, at a location vertically spaced from the plane in which intermediate portion **118** of side wall **42** lies. Horizontal portion **222** of partition **220** includes an aperture **224** therethrough for receiving first end **82** of sender **76**, FIG. 7, so as to allow temperature sender **86** and fluid level sender **88** to be positioned adjacent inner surface **36a** of lower wall **36**. Horizontal portion **222** of partition **220** terminates at edge **226** extending between inner surface **38a** of side wall **38** and upper portion **114** of side wall **42**. Angled portion **228** of partition **220** depends from edge **226** of horizontal portion **222** and is directed towards side wall **40** between side walls **38** and **42**. Angled portion **228** of partition **220** terminates at edge **230**. Vertical portion **232** of partition **220** extends between edge **230** of angled portion **228** of partition **220** and inner surface **40a** of side wall **40**. Partition **220** is configured to maintain adequate hydraulic fluid within lower portion **223** of cavity **46**, and more specifically, to outlet tubes **168** and **170** when sprayer **10** is driven on a sloped surface.

Baffle **240** extends between lower surface **242** of partition **220** and inner surface **36a** of lower wall **36** and between inner surface **40a** of side wall **40** and inner surface **44a** of side wall **44**. Baffle **240** includes a plurality of apertures **244** therethrough and bisects lower portion **223** of cavity **46** into first and second side lower portions **246** and **248**, respectively. Baffle **240** is configured to decrease the velocity of hydraulic fluid flow between first and second side lower portions **246** and **248**, respectively, of lower portion **223** of cavity **48** within storage tank **26** of sprayer **10**, and more specifically, between ports **141**, **143**, **159** and **161** in second side lower portion **248** and suction ports **168** and **170** in first side lower portion **246**, to provide adequate time for air to separate from the hydraulic fluid and to improve mixing and cooling times.

In operation, in order to fill cavity **46** in storage tank **26**, a first end **250** of fill hose **207**, FIG. 2, is fluidically connected to input end **208** of coupling **204** and a second end

252 is fluidically connected to a hydraulic fluid source 254. Hydraulic fluid source 254 provides hydraulic fluid, under pressure to fill hose 207. As heretofore described, valve 212 is moved from the first position to the second position in any conventional manner, such as by the connection of the terminal output end of the fill hose 207 to input end 208 of connector housing 206 of coupling 204 or by the fluidic pressure of the hydraulic fluid delivered to input end 208 of coupling 204. With valve 212 in the second position, hydraulic fluid is allowed to sequentially flow through valve 212, output end 210 of coupling 204 and into passageway 195 through spout 192. The hydraulic fluid continues to flow through passageway 195 and out of inner end 196 of spout 192 into cavity 46 in storage tank 26 until the hydraulic fluid reaches a desired level within cavity 46 in storage tank 26. Thereafter, first end 250 of fill hose 207 is disconnected from input end 208 of coupling, thereby causing valve 212 to return to the first position wherein valve 212 prevents the hydraulic fluid in cavity 46 of storage tank 26 from exiting cavity 26 through coupling 204. As previously noted, the hydraulic fluid in cavity 46 of storage tank 26 may be used to drive various hydraulically driven components 24 of the sprayer (e.g., the steering system, the cylinders controlling the one or more extendable booms, etc.).

It can be appreciated that the above description of a storage tank is merely exemplary of the present invention. Various modes of carrying out the invention are contemplated as being within the scope of the following claims particularly pointing out and distinctly claiming the subject matter, which is regarded as the invention.

We claim:

1. A storage tank for storing hydraulic fluid used to drive hydraulically driven components of an agricultural implement, the storage tank comprising:

an upper wall, a lower wall and a plurality of side walls interconnecting the upper and lower walls, the upper, lower and sidewalls defining a cavity for receiving the hydraulic fluid therein;

a quick connect coupling disposed in the lower wall and having an output end communicating with the cavity and an input end connectable to a hydraulic fluid source;

a partition disposed in the cavity, the partition including a horizontal section dividing the cavity into an upper portion and a lower portion;

a baffle disposed within the lower portion of the cavity and dividing the lower portion of the cavity into first and second side portions, the baffle being generally perpendicular to the horizontal section of the partition and being configured to reduce velocity of hydraulic fluid between first and second side portions during transport of the agricultural implement; and

a unidirectional valve within the quick connect coupling, the valve movable between a first position wherein hydraulic fluid is blocked from flowing from the output end to the input end of the quick connect coupling and a second position wherein hydraulic fluid is allowed to flow from the input end to the output end of the quick connect coupling.

2. The storage tank of claim 1 further comprising a tubular, hydraulic fluid receiving spout extending through the upper wall, the spout defining a passageway having a first end communicating with the cavity and a second end communicating with an environment outside of the storage tank.

3. The storage tank of claim 2 further comprising an end cap receivable on the second end of the spout for selectively closing off the first end of the passageway of the spout.

4. The storage tank of claim 1 further comprising a suction screen defining a passageway having a first end communicating with cavity and a second end communicating with an environment outside of the storage tank.

5. The storage tank of claim 4 wherein the suction screen is one of a plurality of suction screens, each of the suction screens defining a passageway having a first end communicating with cavity and a second end communicating with an environment outside of the storage tank.

6. The storage tank of claim 1 further comprising a cleanout cover positioned in an aperture through one of the side walls of the plurality of side walls.

7. The storage tank of claim 6 wherein the cleanout cover is a cleanout cover and wherein the storage tank further comprises a second cleanout cover positioned in a second aperture through the one of the side walls of the plurality of side walls.

8. A storage system for storing hydraulic fluid used to drive hydraulically driven components of an agricultural implement, comprising:

a tank having an underside and including a cavity in an interior thereof for receiving the hydraulic fluid therein; a partition disposed in the cavity, the partition including a horizontal section dividing the cavity into an upper portion and a lower portion;

a baffle disposed within the lower portion of the cavity and dividing the lower portion of the cavity into first and second side portions, the baffle being generally perpendicular to the horizontal section of the partition and being configured to reduce velocity of hydraulic fluid between first and second side portions during transport of the agricultural implement;

a quick connect coupling operatively connected to the underside of the tank and having an output end in communication with the cavity in the tank and an input end connectable to a hydraulic fluid source; and

a unidirectional valve within the quick connect coupling, the valve movable between a first position wherein hydraulic fluid is blocked from flowing from the output end to the input end of the quick connect coupling and a second position wherein hydraulic fluid is allowed to flow from the input end to the output end of the quick connect coupling.

9. The storage system of claim 8 wherein the tank includes an upper wall, a lower wall and a plurality of side walls interconnecting the upper and lower walls, the lower wall at least partially defining the underside of the tank.

10. The storage system of claim 8 further comprising a tubular, hydraulic fluid receiving spout defining a passageway therethrough, the passageway having a first end communicating with the cavity in the tank and a second end communicating with the output end of the quick connect coupling.

11. The storage system of claim 8 further comprising a tubular, hydraulic fluid receiving spout extending through the tank, the spout defining a passageway having a first end communicating with the cavity and a second end communicating with an environment outside of the storage tank.

12. The storage system of claim 8 further comprising at least one suction screen, the at least one suction screen defining a passageway having a first end communicating with cavity and a second end communicating with an environment outside of the tank.

13. The storage system of claim 8 further comprising at least one cleanout cover positioned within a corresponding aperture in the tank.

* * * * *